



Tubing Inventory Stock List
Carrollton Warehouse

August 2014

Single Wall Polyolefin

DUNBAR-1635F: 2:1 Polyolefin – Flexible
AMS-DTL-23053/5 Class 1 & 3 (Clear is Class 2)

★★ Low Temperature Printable ★★
Prints on all thermal printers

| | | |
|-----------------------------|---------------------|-------------|
| Black, Orange | Spools & 4' Lengths | 3/64" – 5" |
| Clear, Yellow | Spools & 4' Lengths | 3/64" – 4" |
| White, Red | Spools & 4' Lengths | 3/64" – 3" |
| Blue, Green | Spools & 4' Lengths | 3/64" – 2" |
| Brown, Yellow/Green Striped | Spools & 4' Lengths | 3/32" – 1½" |
| Gray, Violet | Spools & 4' Lengths | 3/64" – 1" |

DUNBAR-1635S: 2:1 Polyolefin – Semi-Rigid
AMS-DTL-23053/6 Class 1 (Clear is Class 2)

| | | |
|-------------------------------|---------------------|------------|
| Black, Clear, Optional Colors | Spools & 4' Lengths | 3/64" – 1" |
|-------------------------------|---------------------|------------|

DUNBAR-1625GT: 2:1 Polyolefin – Thin Wall

| | | |
|-------|--------|--------------|
| Black | Spools | 3/64" – 1/4" |
|-------|--------|--------------|

DUNBAR-3635: 3:1 Polyolefin - Flexible
AMS-DTL-23053/5 Class 1 & 3 (Clear is Class 2)

| | | |
|--------------------|--------|---------------------------|
| Black, Clear | Spools | 1.5mm – 50mm (1/16" – 2") |
| White, Red, Yellow | Spools | 3mm – 38mm (1/8" – 1½") |

DUNBAR-4635: 4:1 Polyolefin - Flexible
AMS-DTL-23053/5 Class 1 & 3 (Clear is Class 2)

| | | |
|------------|--------|------------------------|
| Black | Spools | 12mm – 38mm (½" – 1½") |
| White, Red | Spools | 25mm (1") |



Tubing Inventory Stock List
Carrollton Warehouse

September 2012

Dual Wall Polyolefin

| | | |
|---|-------------------------------------|---------------|
| DUNBAR-1625W: AMS-DTL-23053/4 Class 2 | 2:1 Dual Wall Polyolefin – Flexible | |
| Black | 4' Lengths | 1/8" – 1 1/2" |
| | Spools | 1/8" – 1/2" |
| Red | 4' Lengths | 1" |
| Additional Colors | Spools | Various Sizes |

| | | |
|---|-------------------------------------|----------------|
| DUNBAR-3635W: AMS-DTL-23053/4 Class 3 | 3:1 Dual Wall Polyolefin – Flexible | |
| Black, Clear | 4' Lengths | 1/8" – 1 1/2" |
| | Spools | 1/8" – 1/2" |
| Red, White | 4' Lengths | 1/8" – 1 1/2" |
| Yellow, Blue, Green | 4' Lengths | 3/16" – 1 1/2" |

| | | |
|--|---------------------------------------|-----------|
| DUNBAR-3625WS: AMS-DTL-23053/4 Class 1 | 3:1 Dual Wall Polyolefin – Semi-Rigid | |
| Black | 4' Lengths | 1/8" – 1" |

| | | |
|--|-------------------------------------|--------------------------|
| DUNBAR-4635WT: AMS-DTL-23053/4 Class 3 | 4:1 Dual Wall Polyolefin – Flexible | |
| Black | 4' Lengths | 3/16" – 2" |
| | Spools | 3/16" – 1/2"(4mm – 12mm) |
| Clear | 4' Lengths | 5/16" – 2"(8mm – 52mm) |

| | | |
|-----------------------|---------------------------------------|---------------------|
| DUNBAR-4635WS: | 4:1 Dual Wall Polyolefin – Semi-Rigid | |
| Black, Clear | Spools & Cut to Length | 6mm, 8mm (#0, #1) |
| | 4' Lengths & Cut to Length | 11mm, 18mm (#3, #4) |

| | | |
|-----------------------|---------------------------------------|----------------------------------|
| DUNBAR-4650WS: | 4:1 Dual Wall Polyolefin – Semi-Rigid | |
| Black | Spools & Cut to Length | 6mm, 8mm (#0, #1) |
| | 4' Lengths & Cut to Length | 11mm, 13mm, 18mm (#2, #3, #4) |



Tubing Inventory Stock List
Carrollton Warehouse

September 2012

Medium & Heavy Wall Polyolefin

| | | |
|------------------------------------|---|---------------------------|
| DUNBAR-PMWT / PMWT-FR: | 3:1 Medium Wall Adhesive lined Polyolefin | |
| AMS-DTL-23053/15 Class 1 & Class 2 | | |
| Black | 4' Lengths | 7mm – 140mm (0.3" – 5.5") |
| Red | 4' Lengths | 7mm – 43mm (0.3" – 1.7") |

| | | |
|------------------------------------|--|--------------------------|
| DUNBAR-PHWT / PHWT-FR: | 3:1 Heavy Wall Adhesive lined Polyolefin | |
| AMS-DTL-23053/15 Class 1 & Class 2 | | |
| Black | 4' Lengths | 7mm – 130mm (0.3" – 5") |
| Red | 4' Lengths | 7mm – 43mm (0.3" – 1.7") |

| | | |
|---------------------|---|----------------|
| DUNBAR-CATV: | 3:1 Medium Wall Adhesive lined Polyolefin | |
| Black | 4' Lengths | 0.400" – 2.75" |

Specialty Heat Shrink

| | | |
|--------------------------|----------------------------------|------------|
| DUNBAR-FK150: | 2:1 Polyvinylidene Flouride PVdF | |
| AMS-DTL-23053/18 Class 2 | | |
| Clear | Spools | 3/64" – 1" |
| Black | Spools | 1/16" – 1" |

| | | |
|---------------------|---------------------|------------|
| DUNBAR-1675: | 2:1 Kynar | |
| AMS-DTL-23053/8 | | |
| Clear | Spools & 4' Lengths | 3/64" – 1" |
| Black | Spools | 3/64" – 1" |

| | | |
|-----------------------------------|--------------|------------|
| DUNBAR-CRFR: | 2:1 Neoprene | |
| AMS-DTL-23053/1 Class 1 & Class 2 | | |
| Black | Spools | 1/8" – 1½" |

| | | |
|---------------------------|----------------------|--------------|
| DUNBAR-DRET/DR150: | 2:1 Diesel Resistant | |
| AMS-DTL-23053/16 | | |
| Black – DRET - 120°C | Spools | 1/8" – 3/16" |
| Black – DR150 - 150°C | Spools | 3/16" – 1½" |

| | | |
|---------------------|-----------|------------|
| DUNBAR-V200: | 2:1 Viton | |
| AMS-DTL-23053/13 | | |
| Black | Spools | 1/8" – 1½" |



**Tubing Inventory Stock List
Carrollton Warehouse**

September 2012

Teflon Heat Shrink

| | | | |
|---|-----------------|------------|----------------|
| FEP: | FEP Heat Shrink | | |
| AMS-DTL-23053/11 Class 1 (1.3:1 heat shrink) | Natural | 4' Lengths | 24 AWG – 0 AWG |
| AMS-DTL-23053/11 Class 2 (1.6:1 heat shrink) | Natural | 4' Lengths | 3/32" – 2" |

| | | | |
|---|------------------|------------|------------------------------|
| PTFE: | PTFE Heat Shrink | | |
| AMS-DTL-23053/12 Class 2 (2:1 standard wall) | Natural | 4' Lengths | 20 AWG – 0 AWG, 1/8" – 1" |
| AMS-DTL-23053/12 Class 3 (2:1 thin wall) | Natural | 4' Lengths | 30 AWG – 0 AWG, 1/8" – 1" |
| AMS-DTL-23053/12 Class 4 (2:1 light wall) | Natural | 4' Lengths | 30 AWG – 0 AWG |
| AMS-DTL-23053/12 Class 5 (4:1 shrink ratio) | Natural | 4' Lengths | 5/64" – 1.25" |

| | | | |
|--|------------------|------------|--------------|
| ETFE: | ETFE Heat Shrink | | |
| AMS-DTL-23053/14 (1.5:1 shrink ratio) | Natural | 4' Lengths | 3/32" – 1.5" |

| | | | |
|---------------|------------------------------------|-------|-----------------|
| PTFE: | PTFE Non-Shrink (Spaghetti Tubing) | | |
| Standard Wall | Natural | Coils | 30 AWG – 0 AWG, |
| Thin Wall | Natural | Coils | 32 AWG – 0 AWG, |
| Light Wall | Natural | Coils | 32 AWG – 0 AWG, |

PVC Non-Shrink Tubing

| | | | |
|-------------------|----------------------------|------------|--|
| VIT - 600: | PVC Tubing (Non-Shrink) | | |
| Black | Spools (Marked & Unmarked) | 5 AWG – 1" | |
