



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

3-Feb-2015

Product Number : 5152404TFT4

RoHS

**O/A SH CABLE 4/C 24/7 AWG STC
SR-PVC Insulation
Gray PVC FT-4 Jacket**

Conductor : 24 AWG 7 Strand STC Cond.	
Total Cable Weight : 25 kg/km	Final Diameter : 0.148 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield 0.5	
Drain: 24 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 26.1 @ 25°C Ohms / 1000	Mutual Capacitance : 29.8 pF/ft
Impedance : 70 Ohms	Cond to Shield Cap. : 53.4 pF/ft
Velocity of Prop : 65 %	Inductance. : 1.3 mH/km

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C
600V FT-4 (UL) CMG E132883 105°C #24 AWG RoHS

(All of the above values are approximated to within +/- 10%)

5152404TFT4