



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: sales@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

2-Dec-2019

Product Number : 5152405TFT4

RoHS

Overall Shielded Cable 5/C 24/7 AWG Stranded Tinned Copper
SR-PVC Insulation
PVC FT-4 Jacket
Operating Temperature: -20 to 105°C

General Specification of Product :

Final Diameter :	0.155 inches	3.937 mm
Total Cable Weight:	25 kg/km	17 lbs/1000 ft
Conductor :	24 AWG 7 Stranded Tinned Copper Conductor	
Insulation :	SR-PVC	
Shield :	Overall Foil Shield	
Drain \ Ground:	24 AWG 7 Stranded Tinned Copper Conductor	
Outer Jacket :	PVC FT4	
Outdoor Rating :	Sunlight Resistant	

Certification and Approvals : 105°C FT4 CSA CMG, UL CMG

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C SUN RES LL61365 OR CSA AWM II A/B
105°C 600V FT4 (UL) CMG E132883 105°C #24 AWG ROHS

Electrical Characteristics :

DC Resistance 25°C:	26.1 Ohms / 1000 ft
Mutual Capacitance :	28.9 pF/ft
Cond to Shield Cap. :	53.5 pF/ft
Impedance :	70 Ohms
Velocity of Prop :	65 %
Inductance. :	1.3 mH/km

Additional Information :

Please contact Sales regarding Finished Lengths, Insulation and Jacket Colours.

All Cables are Canadian Made in Ontario

QMS Registered ISO 9001

Electro Cables Inc. has been manufacturing quality cables for over 30 years.

(All of the above values are approximated to within +/- 10%)

5152405TFT4