



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896  
Fax: 613-394-4101 email: info@electrocables.com  
Mailing: P.O. Box 276, Trenton, ON K8V 5R5  
www.electrocables.com

2-Dec-2011

**Product Number : 5152410TFT4**

**RoHS**

**O/A SH CABLE 10/C 24/7 AWG STC  
SR-PVC Insulation  
0 PVC FT-4 Jacket**

Conductor : 24 AWG 7 Strand STC Cond.	
Total Cable Weight : 54 kg/km	Final Diameter : 0.216 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield 0.75	
Drain : 24 AWG 7 Strand STC Cond.	
DC Resistance : 25.9 Ohms	Mutual Capacitance : 26.8 pF/ft
Impedance : 78.0 Ohms	Shielded Cap. : 48.5 pF/ft
Velocity of Prop : 62 %	Inductance. : 1.5 mH/km

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C  
600V FT-4 (UL) CM E132883 105°C #24 AWG RoHS

*(All of the above values are approximated to within 10%)*