



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896  
Fax: 613-394-4101 email: info@electrocables.com  
Mailing: P.O. Box 276, Trenton, ON K8V 5R5  
www.electrocables.com

3-Feb-2015

**Product Number : 5152415TFT4**

**RoHS**

**O/A SH CABLE 15/C 24/7 AWG STC  
SR-PVC Insulation  
Gray PVC FT-4 Jacket**

|   |                                  |
|---|----------------------------------|
| Conductor : 24 AWG 7 Strand STC Cond.   |                                  |
| Total Cable Weight : 72 kg/km           | Final Diameter : 0.244 inches    |
| Insulation : SR-PVC                     | Jacket : PVC                     |
| Shield : Foil Shield 1.0                |                                  |
| Drain: 24 AWG 7 Strand STC Cond.        |                                  |
| DC Resistance 25°C: 26.5 Ohms / 1000 ft | Mutual Capacitance : 25.5 pF/ft  |
| Impedance : 80 Ohms                     | Cond to Shield Cap. : 48.6 pF/ft |
| Velocity of Prop : 64 %                 | Inductance. : 1.3 mH/km          |

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C  
600V FT-4 (UL) CMG E132883 105°C #24 AWG RoHS

( All of the above values are approximated to within +/- 10% )

5152415TFT4