



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 73-325

CONSTRUCTION SPECIFICATIONS

| | |
|-------------------------------|---|
| Description | AWM 25C 24 AWG Shielded |
| Conductor | 24 AWG 7 Strand Tinned Copper - Concentric |
| Conductor Diameter | 0.024" |
| Insulation Type | Semi Rigid PVC |
| Insulation Thickness | 0.009" |
| Cable Assembly | Conductors are cabled together with an overall shield and drain wire. (foil out, drain out) |
| Drain Wire | 24 AWG 7 Strand Tinned Copper - Concentric |
| Overall Shielding Tape | Aluminum/mylar |
| Ripcord | Polyester Ripcord included under the cable jacket |
| Jacket | Flame Retardant PVC |
| Jacket Thickness | 0.030" (minimum average) |
| Overall Cable Diameter | 0.326" |
| Jacket Print | CSA AWM II A/B105C 600V FT4 LL67097 CMG 24 AWG 60C LL83251 RU AWM STYLE 2464 80C 300V E111002 ROHS (work order) |

ELECTRICALS

| | |
|-----------------------------|--|
| Voltage | 300V; CMG, AWM STYLE 2464 / 600V; AWM II |
| Conductor Resistance | 25.7 Ohms/Mft @20C |

CERTIFICATIONS AND PHYSICAL PROPERTIES

| | |
|------------------------------|---|
| CSA Certified | *CSA C22.2 No. 214, Communications Cables *CSA C22.2 No. 210.2, Appliance Wiring Material Products |
| UL Recognized | *UL 758, Appliance Wiring Material |
| Flame Test Rating | CSA FT4 |
| Temperature Rating | 60C; CMG, / 105C; AWM II / 80C; AWM STYLE 2464 |
| ROHS | Compliant |
| Cable Weight | 99.70 kg/km |
| Copper Content | 47.16 kg/km |
| Max Pull Tension | 56 kgs |
| Min Bending Radius | 4.00 inches (installed) |
| Min Installation Temp | -20C |

Rev. 000

7-Dec-11