

3 PAIR 16 AWG FOIL SHIELDED AUDIO/ DATA CABLE

Applications: Computer, EIA RS-232, Data Transmission, Audio,
Broadcast, Electronic and Instrumentation

Part No.	38703
CONDUCTOR	16 awg (26 x 30) Tinned Copper O.D.: 0.060" (1.52 mm)
INSULATION	0.015" (0.38 mm) Semi-Rigid Polyvinylchloride (SR-PVC) Colour Code: P1: Black/Red P2: Black/White P3: Black/Green
SHIELD	Aluminum Foil 100% Coverage
DRAIN WIRE	18 awg Stranded Tinned Copper
JACKET	0.030" (0.76 mm) Gray Polyvinylchloride (PVC)
OVERALL DIAMETER	0.390" (9.91 mm)
WEIGHT	98 lbs/Mft (146 kgs/km)
TEMPERATURE RATING	-20°C to +105°C
VOLTAGE	600 Volts
APPROVALS	CSA AWM A/B 105°C 600 Volt FT4 CSA CMG UL CM

38703

DRAWING NO.

ALL DIMENSIONS NOMINAL UNLESS SPECIFIED AND SUBJECT TO CHANGE WITHOUT NOTICE

REVISION	APPD	DATE



DELCO WIRE AND CABLE LIMITED
1 Saramia Crescent Concord, Ontario L4K 3S6

DRWN	CM	DATE
		03/07/07
CHKD	<i>JA</i>	<i>3/7/07</i>
APPD	<i>GS</i>	<i>03/07/07</i>