



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2000

PRODUCT DATA SHEET

Part No: 74-986

CONSTRUCTION SPECIFICATIONS

Description	AWM 2C 20 AWG Unshielded
Conductor	20 AWG 7 Strand Tinned Copper - Concentric
Conductor Diameter	0.038"
Insulation Type	Flame Retardant PVC
Insulation Thickness	0.015"
Conductor Identification	Black, Red
Ripcord	Polyester Ripcord included under the cable jacket
Jacket	Flame Retardant PVC
Jacket Thickness	0.033" (minimum average)
Overall Cable Diameter	0.215"
Jacket Print	CSA AWM II A/B105C 300V FT4 LL67097 RU AWM STYLE 2464 80C E111002 ROHS (work order)

ELECTRICALS

Voltage	300V
Conductor Resistance	10.3 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	*CSA C22.2 No. 210.2, Appliance Wiring Material Products
UL Recognized	*UL 758, Appliance Wiring Materials
Flame Test Rating	CSA FT4
Temperature Rating	80C; STYLE 2464 / 105C; AWM II
ROHS	Compliant
Cable Weight	32.05 kg/km
Copper Content	9.46 kg/km
Max Pull Tension	11.00 kgs
Min Bending Radius	2.75 inches (installed)
Min Installation Temp	-20C

Rev. 000

11-Feb-09