Deca Cables Inc.

150 North Murray Street PO Box 777 Trenton, ON Canada K8V 5W6

Telephone: (613) 392-3585 Fax: (613) 392-7908 ISO 9002 - 1994

PRODUCT DATA SHEET

PART NUMBER 76-970

DESCRIPTION 10/C 26 AWG 80% TINNED BRAID

CONDUCTOR 26 AWG BARE COPPER

STRANDING 7 X 0.0063"

CONDUCTOR DIAMETER 0.019"

RESISTANCE 37.3 OHMS/1000FT

INSULATION SR PVC

INSUL. COND. DIAMETER 0.038"

BRAID SHIELD TINNED COPPER BRAID, 80% COVERAGE

CONDUCTOR ASSEMBLY CONDUCTORS ARE TWISTED TOGETHER WITH FILLERS

AS REQUIRED TO MAKE ROUND. OVERALL MYLAR

JACKET PVC

JACKET THICKNESS 0.030"

FINISHED DIAMETER 0.247"

FLAME RATING FT1

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.

Rev. 0 2001.03.09