

# 21 AWG SINGLE CONDUCTOR

<b>Part No.</b>	<b>392444</b>
CONDUCTOR	21 awg (7 x 0.011") Composite 4 Strands Tinned Copper 3 Strands Galvanized Steel Resistance: 20.3 Ohms/Mft (66.6 Ohms/km)
INSULATION	Minimum/Average 0.032" (0.81 mm) Soft Yellow Polyvinylchloride (PVC 105°C) Resistance: Greater than 3,000 Megohms/Mft
OVERALL DIAMETER	0.104" (2.64 mm)
CONDUCTOR BREAK STRENGTH	80 lbs (80,000 PSI, Calculated Value)
INSULATION TENSILE STRENGTH	1,500 PSI
INSULATION ELONGATION	250%
WEIGHT	6.2 lbs/Mft (9.2 kgs/km)
VOLTAGE	600 Volts
TEMPERATURE	105°C

**392444**  
DRAWING NO.

ALL DIMENSIONS NOMINAL UNLESS SPECIFIED AND SUBJECT TO CHANGE WITHOUT NOTICE

**RoHS COMPLIANCE:** Please be advised that Delco Wire #392444 does not contain the following restricted substances according to European Directive 2002/95/EC (RoHS):  
 Lead and Lead Compounds      Mercury and Mercury Compounds      Cadmium and Cadmium Compounds  
 Hexavalent Chromium Compounds      Polybrominated Bipenyls (PBB)      Polybrominated Diphenyl Ethers (PBDE)  
 This is presented in good faith and is believed to be reliable and accurate. However, because information presented in whole or part by other parties is beyond our control, no warranty, expressed or implied, is given by Delco Wire and Cable Limited. Delco Wire and Cable Limited assumes no liability for results obtained or damages incurred through the application of data presented.

REVISION	APPD	DATE
A	<i>BB</i>	<i>May 26/09</i>



**DELCO WIRE AND CABLE LIMITED**  
1 Saramia Crescent Concord, Ontario L4K 3S6

DRWN	CM	DATE
		05/07/09
CHKD	<i>BB</i>	<i>05/07/09</i>
APPD	<i>BB</i>	<i>05/7/09</i>