



DECA CABLES INC.
150 North Murray Street
P.O. Box 777
Trenton, Ontario K8V 5W6
Canada

Telephone: (613) 392-3585

Fax: (613) 392-7908

ISO 9001 - 2000

PRODUCT DATA SHEET

PART NUMBER	73-587
DESCRIPTION	LOW CAPACITANCE FOAM/PVC 1PR 26 AWG SHIELDED FT4
CONDUCTOR	26 AWG TINNED COPPER
STRANDING	7 x 0.0063"
CONDUCTOR DIAMETER	0.019"
CONDUCTOR RESISTANCE	42.5 OHMS/1000 FT
INSULATION	CELLULAR POLYETHYLENE
INSULATION THICKNESS	0.016"
INSUL. COND. DIAMETER	0.053"
CAPACITANCE	11 PF/FT (conductor to conductor)
CHARACTERISTIC IMPEDANCE	110 OHMS
CONDUCTOR ASSEMBLY	CONDUCTORS ARE TWISTED TOGETHER WITH AN OVERALL SHIELD AND DRAIN. (ALUMINUM SIDE IN, DRAIN IN)
SHIELD	ALUMINUM/MYLAR
DRAIN WIRE	24 AWG 7 X 0.008" TINNED COPPER
JACKET	PVC
JACKET THICKNESS	0.013"
RIPCORD	POLYESTER RIPCORD UNDER JACKET
FINISHED DIAMETER	0.142"
CSA CERTIFIED	CMG
UL RECOGNIZED	AWM STYLE 2960
FLAME RATING	FT4
ROHS	COMPLIANT

The material contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary and material quality or information that may be provided in whole or part by others may be beyond our control, no warranty, expressed or implied, is given and Deca Cables Inc. can assume no liability for results obtained or damages incurred through the application of the data and tests presented.

Rev. 1

2006.05.17