

Aerospace Part#: 5120pvgray

LOW CAP CABLE

DESCRIPTION

1 Pair AWG 24/7x32 TC
Overall Foil Shield FoamFEP/PVC Gray CL2P CMP

PHYSICAL PROPERTIES

Pairs

Insulation

# Pairs	AWG	Material	Material	Wall	Finished OD
1	24/7x32	Tinned Copper	Foam FEP	.015"	.054"

Outer Shield Material

Drain Wire

Shield Type	Material	Coverage	AWG	Material
Overall Foil Shield	Alum / Mylar	100%	24/7x32	Tinned Copper

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
LS PVC	Gray	.015"	.142" Nom.	2" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -5C to 75C	11.8 lbs/m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage	Capacitance (Cond. To Cond.)	Impedence
UL Rated 300V Power Ltd.	12.5 pf / ft nom.	110 ohms nom.

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

RoHS Compliant	YES
Suitability	Indoor
Resistance	Sunlight
Applications	Communications, Audio, Control, Instrumentation, Remote, Signaling, Power-limited systems
Flame Test	NFPA 262 / FT6
NEC / (UL) Specification	CL2P / CMP
CEC / C (UL) Specification	CMP

MISCELLANEOUS

Markings: "CLARITY" BY DELCO WIRE #394057GRAY 1 PR 24 AWG 110 OHM DIGITAL AUDIO (UL) CMP CL2P C(UL) (seq.# 1-9999)

Color: Black/Red
Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice