



MERCURY WIRE PRODUCTS, INC.
SPENCER, MASSACHUSETTS
Manufacturers of Wire & Cable

CABLE SPECIFICATION

MW#: 20331
ENGINEERED BY: MA
DATE: 8/26/2004
SHEET 1 OF 1
REVISION: 01

9/C #24 AWG CABLE

Conductors: #24 AWG 7/32 tinned copper

Insulation: nominal .010" thickness, polypropylene

- Color Code:**
1. Red
 2. White
 3. Green
 4. Blue
 5. Brown
 6. Yellow
 7. Orange
 8. Black
 9. Gray

Cabling Construction: (9) #24 AWG conductors are cabled together and the cable bundle is wrapped with an overall aluminum/polyester shield, foil facing in making contact with the drain wire.

Drain Wire: #24 AWG 7/32 tinned copper

Fillers: fillers may be used as required for roundness.

Jacket: nominal .025" thickness, black polyurethane


Approximate OD: .215"

*Print - Inkjet
Deleo Wire And Cable Ltd
397234*

Cross Section

POLYURETHANE JKT

ALUMINUM/POLYESTER SHIELD
(FOIL IN)



#24 AWG DRAIN WIRE

FILLERS

#24 AWG CONDUCTORS

PACKAGING: BULK PUT-UPS, LONGEST LENGTHS POSSIBLE, 3 LENGTHS PER REEL MAXIMUM UNLESS OTHERWISE SPECIFIED ON PURCHASE ORDER. DIFFERENT PACKAGING MAY INCUR ADDITIONAL COSTS.

THE PHYSICAL AND ELECTRICAL CHARACTERISTICS CONTAINED IN THIS CABLE SPECIFICATION ARE BELIEVED TO BE RELIABLE AND ARE DERIVED FROM VENDOR SUPPLIED DATA AND INDUSTRY STANDARDS. AS EACH APPLICATION IS UNIQUE, MERCURY WIRE CAN MAKE NO WARRANTIES AS TO THE SUITABILITY OF ANY PRODUCT FOR A PARTICULAR USE.

ACCEPTED: *Deleo Wire And Cable Ltd*
COMPANY NAME

Bill Jesso
NAME (PRINTED)

08-30-04
DATE

[Signature]
NAME (SIGNATURE)

