

“Stay Connected” with



Liquid Tight Cordgrips

a PennEngineering® Company



HEYbrid™ Brass/Nylon Liquid Tight Cordgrips

Straight-Thru, NPT Hubs




Don't get SKU'ed: More Cable Range, Fewer SKU's –
The Ultimate in Liquid Tight Strain Relief Protection



- **HEYCo-molded gripping finger/gland technology** accommodates the **widest cable range** over the **fewest sku's**.
- Rolled grease-free threads **prevent galling** and allow for multiple assemblies and disassemblies. No messy, unsightly thread lubrication required.
- Approved for **NEMA 4, 4X, 6 and 6P** applications.
- Self-retaining sealing rings eliminate the need for an O-Ring groove, thus **reducing cost**.
- Sealing washer required for through hole applications only.
- Typical applications: Control cabinets, car washes, hot tubs, instrumentation, carpet cleaning machines, underground for direct burial or submersed up to 130 ft. (70 PSIG).
- Constructed from corrosion resistant Nickel Plated Brass.
- Resistant to salt water, acids and most chemicals.
- Patent pending.
- DFARS Compliant

CABLE DIA. RANGE				PART NO.	DESCRIPTION	UL or RA	PART DIMENSIONS							
Minimum		Maximum					A	B		C		D		
in.	mm.	in.	mm.			Clearance Hole Dia.	Max. O.A. Length	Thread Length	Wrenching Flat Size	in.	mm.	in.	mm.	
HEYCo-molded Finger/Gland														
.065	1,7	.210	5,3	M5900	RNBCG 1/4 NPT	cULus	.540	13,7	1.29	32,8	.40	13,2	.75	19,1
.115	2,9	.250	6,4	M5901	NBCG 1/4 NPT	cULus	.680	17,3	1.39	35,3	.41	10,4	.88	22,4
.065	1,7	.230	5,8	M5902	RNBCG 3/8 NPT	cULus	.680	17,3	1.39	35,3	.41	10,4	.88	22,4
.105	2,7	.315	8,0	M5903	NBCG 3/8 NPT	cULus	.875	22,2	1.69	42,9	.53	13,5	1.06	26,9
.095	2,4	.290	7,4	M5906	RNBCG 1/2 NPT	cULus	.875	22,2	1.69	42,9	.53	13,5	1.06	26,9
.170	4,3	.450	11,4	M5907	NBCG 1/2 NPT	cULus	.875	22,2	1.81	46,0	.53	13,5	1.25	31,8
.180	4,6	.400	10,1	M5908	RNBCG LL 1/2 NPT	cULus	.875	22,2	1.81	46,0	.53	13,5	1.25	31,8
.260	6,6	.545	13,8	M5909	NBCG LL 1/2 NPT	cULus	1.109	28,2	1.93	49,0	.55	14,0	1.31	33,3
.250	6,4	.490	12,4	M5910	RNBCG 3/4 NPT	cULus	1.109	28,2	1.93	49,0	.55	14,0	1.31	33,3
.435	11,0	.705	17,9	M5911	NBCG 3/4 NPT	cULus	1.375	34,9	2.29	58,1	.69	17,5	1.75	44,5
.490	12,4	.785	19,9	M5912	RNBCG 1 NPT	cULus	1.375	34,9	2.29	58,1	.69	17,5	1.75	44,5
.590	15,0	1.000	25,4	M5913	NBCG 1 NPT	cULus								

The HEYCo-molded Finger, Gland & Seat



Quick Specs

Material	Nickel Plated Brass Body and sealing nut with nylon 6/6 and TPE co-molded finger/gland assembly SBR Sealing Washer
Certifications	cULus Certified by UL for Compliance with both Canadian and U.S. requirements under File E51579. cRAus Recognized under the Component Program of Underwriters' Laboratories File E51579 to both Canadian and U.S. requirements
Flammability Rating	94V-2
Temperature Range	-40°F (-40°C) to 221°F (105°C)
IP Rating	IP68 (70 PSI, 5 BAR)