

“Stay Connected” with



Liquid Tight Cordgrips

a PennEngineering® Company



Heyco® -Tite Brass Liquid Tight Clamping Cordgrips

Metric Hubs

The Ultimate in Liquid Tight Strain Relief Protection

- Extra pull-out resistance for applications requiring maximum strain relief in addition to liquid tight sealing.
- IP 68 and IP 69 rated.
- For non-liquid tight Heyco Brass Clamping Strain Reliefs, see page 4-35.
- Available by special order only.
- Locknuts not included. For metal locknut specifications or to order locknuts separately, see page 3-48.



CABLE DIA. RANGE				PART NO.	THREAD SIZE	SEALING INSERT PIECES	PART DIMENSIONS							
Minimum		Maximum					A Clearance Hole Dia.		B Max. O.A. Length		C Thread Length		D Wrenching Flat Size	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.	in.	mm.

Standard Threads

.118	3,0	.157	4,0	14850	M10 x 1,5	1	.394	10,0	1.34	34,0	.39	10,0	.51/.63	13/16
.157	4,0	.236	6,0	14851										
.197	5,0	.256	6,5	14852	M12 x 1,5	1	.472	12,0	1.42	36,0	.39	10,0	.59/.63	15/16
.256	6,5	.315	8,0	14853										
.236	6,0	.413	10,5	14854	M16 x 1,5	2	.630	16,0	1.57	40,0	.39	10,0	.71/.75	18/19
.315	8,0	.591	15,0	14855	M20 x 1,5	2	.787	20,0	1.61	41,0	.39	10,0	.94	24
.492	12,5	.807	20,5	14856	M25 x 1,5	2	.984	25,0	1.81	46,0	.43	11,0	1.18	30
.669	17,0	1.004	25,5	14857	M32 x 1,5	2	1.260	32,0	2.09	53,0	.51	13,0	1.42	36
.945	24,0	1.299	33,0	14858	M40 x 1,5	2	1.575	40,0	2.24	57,0	.51	13,0	1.81	46
1.299	33,0	1.654	42,0	14859	M50 x 1,5	2	1.968	50,0	2.48	63,0	.55	14,0	2.17	55
1.575	40,0	2.047	52,0	14860	M63 x 1,5	2	2.480	63,0	2.72	69,0	.55	14,0	2.76	70
1.968	50,0	2.480	63,0	14861	M75 x 1,5	2	2.953	75,0	2.80	71,0	.59	15,0	3.15	80

Short Threads

.118	3,0	.157	4,0	14862	M10 x 1,5	1	.394	10,0	1.14	29,0	.20	5,0	.51/.63	13/16
.157	4,0	.236	6,0	14863										
.197	5,0	.256	6,5	14864	M12 x 1,5	1	.472	12,0	1.22	31,0	.20	5,0	.59/.63	15/16
.256	6,5	.315	8,0	14865										
.236	6,0	.413	10,5	14866	M16 x 1,5	2	.630	16,0	1.38	35,0	.20	5,0	.71/.75	18/19
.315	8,0	.591	15,0	14867	M20 x 1,5	2	.787	20,0	1.46	37,0	.24	6,0	.94	24
.492	12,5	.807	20,5	14868	M25 x 1,5	2	.984	25,0	1.65	42,0	.28	7,0	1.18	30
.669	17,0	1.004	25,5	14869	M32 x 1,5	2	1.260	32,0	1.89	48,0	.31	8,0	1.42	36
.945	24,0	1.299	33,0	14870	M40 x 1,5	2	1.575	40,0	2.05	52,0	.31	8,0	1.81	46
1.299	33,0	1.654	42,0	14871	M50 x 1,5	2	1.968	50,0	2.28	58,0	.35	9,0	2.17	55
1.575	40,0	2.047	52,0	14872	M63 x 1,5	2	2.480	63,0	2.56	65,0	.39	10,0	2.76	70
1.968	50,0	2.480	63,0	14873	M75 x 1,5	2	2.953	75,0	2.64	67,0	.43	11,0	3.15	80



Quick Specs

Material
Certifications
Temperature Range
IP Rating



Nickel-Plated Brass Body w/TPE Seal, NBR O-ring and Stainless Steel Screws
Marks License #40019686
-40°F (-40°C) to 212°F (100°C)
IP 68, IP 69K