

# 3 CONDUCTOR 18 AWG UNSHIELDED CABLE PLENUM

**407054/YEL**  
DRAWING NO.

<b>Part No.</b>	<b>407054/YEL</b>
CONDUCTOR	18 awg (7 x 26) Tinned Copper O.D.: 0.048" (1.22 mm)
INSULATION	0.015" (0.38 mm) Fluorofoam O.D.: 0.078" (1.98 mm) Colour Code: Black, Red & White
TWIST LAY	Cable 3 Conductors 4" Lay O.D.: 0.167" (4.24 mm)
JACKET	0.015" (0.38 mm) Yellow Halar 930
OVERALL DIAMETER	0.197" (5.00 mm)
IMPEDANCE	100 Ohms
CAPACITANCE	12.5 pF/ft (41.0 pF/m)
VELOCITY OF PROPAGATION	78%
TEMPERATURE RATING	-40°C to 150°C
VOLTAGE	300 Volts
MARKING	E102194 CL2P OR CMP 18 AWG 150C (UL) C(UL) FT6

**ALL DIMENSIONS NOMINAL UNLESS SPECIFIED AND SUBJECT TO CHANGE WITHOUT NOTICE**

**ACCEPTED:** \_\_\_\_\_  
COMPANY NAME

NAME (PRINTED) \_\_\_\_\_ DATE \_\_\_\_\_

NAME (SIGNATURE) \_\_\_\_\_



DRWN	CM	09/06/07
CHKD	<i>AB</i>	<i>Sept 14/07</i>
APPD	<i>John</i>	<i>09-14-07</i>

**DELCO WIRE AND CABLE LIMITED**  
1 Saramia Crescent Concord, Ontario L4K 3S6

# 3 CONDUCTOR 18 AWG UNSHIELDED CABLE PLENUM

Part No.

407054/YEL

REVISION	DESCRIPTION	APPD	DATE
A	Change in Manufacturing	TAB	JAN 13/12

**407054/YEL**  
DRAWING NO.

ACCEPTED: \_\_\_\_\_  
COMPANY NAME

NAME (PRINTED) \_\_\_\_\_ DATE \_\_\_\_\_

NAME (SIGNATURE) \_\_\_\_\_



**DELCO WIRE AND CABLE LIMITED**  
1 Saramia Crescent Concord, Ontario L4K 3S6

**DELCO WIRE AND CABLE LIMITED**  
1 Saramia Crescent Concord, Ontario L4K 3S6