

4 CONDUCTOR 18 AWG FOIL SHIELDED CABLE PLENUM

407055/YEL
DRAWING NO.

Part No.	407055/YEL
CONDUCTOR	18 awg (7 x 26) Tinned Copper O.D.: 0.048" (1.22 mm)
INSULATION	0.030" (0.76 mm) Fluorofoam O.D.: 0.108" (2.74 mm) Colour Code: Black, Red, White & Green
TWIST LAY	Cable 4 Conductors 4" Lay O.D.: 0.256" (6.50 mm)
FOIL SHIELD	Aluminum/Mylar (foil side in)
DRAIN WIRE	20 awg (7 x 28) Tinned Copper O.D.: 0.260" (6.60 mm)
JACKET	0.015" (0.38 mm) Yellow Halar 930
OVERALL DIAMETER	0.290" (7.37 mm)
IMPEDANCE	100 Ohms
CAPACITANCE	12.5 pF/ft (41.0 pF/m)
VELOCITY OF PROPAGATION	78%
TEMPERATURE RATING	-40°C to 150°C
VOLTAGE	300 Volts
MARKING	E102194 CL2P OR CMP 18 AWG 150C (UL) C(UL) FT6

ALL DIMENSIONS NOMINAL UNLESS SPECIFIED AND SUBJECT TO CHANGE WITHOUT NOTICE

ACCEPTED: _____
COMPANY NAME

NAME (PRINTED) _____ DATE _____

NAME (SIGNATURE) _____



DRWN	CM	09/06/07
CHKD	<i>BB</i>	<i>Sept 14/07</i>
APPD	<i>John</i>	<i>09-14-07</i>

DELCO WIRE AND CABLE LIMITED
1 Saramia Crescent Concord, Ontario L4K 3S6

4 CONDUCTOR 18 AWG FOIL SHIELDED CABLE PLENUM

Part No. 407055/YEL

REVISION	DESCRIPTION	APPD	DATE
A	Change in Manufacturing	TAB	JAN 13/12

407055/YEL
DRAWING NO.

ACCEPTED: _____
COMPANY NAME

NAME (PRINTED) _____ DATE _____

NAME (SIGNATURE) _____



DELCO WIRE AND CABLE LIMITED
1 Saramia Crescent Concord, Ontario L4K 3S6

DELCO WIRE AND CABLE LIMITED
1 Saramia Crescent Concord, Ontario L4K 3S6