



PRODUCT DATA SHEET

Group Number:	4342
Description:	22 7/30 TC UL AWM 1007/1569 CSA TR64 or AWM I A/B
Nominal OD:	0.063" +/- 0.005"
Nominal Wall:	0.015"
Copper Conductor:	22 7/30 TC 0.7" LHL
Insulation:	PVC
UL Temperature and Voltage Ratings:	AWM 1007: 80C Dry, 60C Oil, 300 Vac AWM 1569: 105C Dry, 300 Vac
CSA Temperature and Voltage Ratings:	TR64: 90C, 300 volts AWM: 105C, 300 volts
Print:	22 AWG UR AWM STYLE 1569 105°C OR AWM STYLE 1007 80°C VW1 * DIXIEWIRE (C) * CSA TR64 90C FT1 OR AWM I A 105°C 300V FT1

ROHS Compliance:

DixieWire Company and our key suppliers support the European Union Directive 2002/95/EC (RoHS) that restricts the use of certain hazardous substances in the design and manufacture of Electrical and Electronic Equipment. We have investigated the materials used in the manufacture of our products for the presence of substances restricted by European Union Restriction of Hazardous Substance Directive, citation 2002/95/EC. The substances covered by this investigation and the limits used are:

Lead	0.1%
Mercury	0.1%
Cadmium	0.01%
Chromium VI	0.1%
Polybrominated biphenyls (PBB)	0.1%
Polybrominated diphenyl ethers (PBDE)	0.1%

For product manufactured on or after March 1, 2006, during manufacturing we do not use or intentionally incorporate into the product any of the above substances in amounts which exceed the applicable limits. Trace levels could be present as contaminants.