



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: info@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

31-Jan-2013

Product Number : 548245185TFT4

RoHS

**Foil & Braid Shielded 1/PR 24/7 AWG STC
LO-CAP F.P.O. 75'C Insulation
Gray PVC FT4 Jacket**

Conductor :	24 AWG 7 Strand STC Cond.		
Total Cable Weight :	33 kg/km	Final Diameter :	0.182 inches
Insulation :	FPO	Jacket :	PVC
Shield :	Foil Shield 0.625		
Drain :	24 AWG 7 Strand STC Cond.		
DC Resistance :	26.2 @ 25°C Ohms	Mutual Capacitance :	19.0 pF/ft
Impedance :	100 Ohms	Cond to Shield Cap. :	34.8 pF/ft
Velocity of Prop :	63 %	Inductance. :	1.6 mH/km

Print Notes :

Standard Print : ECI ELECTROLENE LOW CAP c CSA us CMG 75°C LL61365 OR CSA AWM II A 75°C 150V FT-4 LOW VOLTAGE COMPUTER CABLE 24 AWG RoHS

(All of the above values are approximated to within 10%)