



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 76-979

CONSTRUCTION SPECIFICATIONS

Description	2 Pair 24 AWG OAS, 90% Braid Shield
Conductor	24 AWG 7 Strand Tinned Copper - Concentric
Conductor Diameter	0.024"
Insulation Type	High Density Polyethylene
Insulation Thickness	0.026"
Pair Identification	White/Blue & Blue/White, White/Orange & Orange/White
Overall Shielding Tape	Aluminum/mlyar
Drain Wire	24 AWG 7 Strand Tinned Copper - Concentric
Cable Assembly	Conductors are paired then cabled together with an overall aluminum/ shield and drain (foil out, drain out). A tinned copper braid shield is applied over the cabled assembly.
Braid Shield	36 AWG Tinned Copper Braid, 90% Coverage
Ripcord	Polyester Ripcord included under the cable jacket
Jacket	Flame Retardant PVC
Jacket Thickness	0.030" (minimum average)
Overall Cable Diameter	0.353"
Jacket Print	LOW CAPACITANCE CSA CMG 24 AWG FT4 60C LL83251 RU AWM STYLE 2919 80C LOW VOLTAGE COMPUTER CABLE E111002 ROHS

ELECTRICALS

Voltage	300V; CMG / 30V; AWM STYLE 2919
Conductor Resistance	26.28 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	*CSA C22.2 No. 214, Communications Cables
UL RECOGNIZED	*UL 758, Appliance Wiring Material
Flame Test Rating	CSA FT4
Temperature Rating	60C; CMG / 80C; AWM STYLE 2919
ROHS	Compliant
Cable Weight	74.92 kg/km
Copper Content	35.2 kg/km
Max Pull Tension	9 kgs
Min Bending Radius	4.25 inches (installed)
Min Installation Temp	-20C