



# PRODUCT DATA SHEET

1530 Shields Drive  
Waukegan, IL 60185  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

PART NUMBER: 44258  
DESCRIPTION: 12/2 W/GND FLAT PUMP CABLE  
CONSTRUCTION: This cable consists of three bare copper insulated conductors laid parallel with an overall jacket.  
APPROVALS: UL Standard 83 (Ins. Walls), Overall Cable UL Listed Misc. Wires Submersible Pump Cable  
APPLICATION: Underwater pumps and similar applications.

---

## Construction Parameters:

Conductor	12 AWG Bare Copper
Stranding	65/30
Insulation Material	TPE
Insulation Thickness	0.031" Nom.
Insulated Conductor Diameter	0.154" Nom.
Number of Conductors	3
Lay Length	Parallel
Jacket Material	TPE
Jacket Thickness	0.030" Nom.
Overall Cable Diameter	0.216" x 0.526" Nom.
Approximate Cable Weight	95.0 Lbs/1M' Nom.

---

## Electrical Properties:

Temperature Rating	-50°C to 90°C Dry, 75°C Wet
Operating Voltage	600 V RMS Max.
DC Resistance per Conductor @ 20°C	1.589 Ohms/1M' Nom.

---

Insulation Colors	Black Red Green
Jacket Color	Black or Blue

Legend (Surface Ink Print)	COLEMAN CABLE E54868 12 AWG (UL) 600V PUMP CABLE 90C DRY 75C WET
----------------------------	---

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name \_\_\_\_\_

Customer Approval \_\_\_\_\_

Specification Issue Date: January 20, 2004