

U.I. Lapp GmbH	PRODUCT INFORMATION	
	EPIC® POWER LS1 Contacts female	05.11.2015

Contacts, tools, accessories for circular connectors



Good chemical resistance



Wide clamping range



Corrosion-resistant



Maximum vibration protection



Mechanical resistance



Oil-resistant



Optimum strain relief



Robust



Reliability



Info

All contacts are high quality gold plated

Contacts are designed for wide crimping range, therefore low number of variants

Only available as crimp version due to the high mechanical stress in servo applications

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: LAPP_PRO136968EN.pdf	1 / 3
--------------------	--------------------------------	-------

EPIC® POWER LS1 Contacts female

05.11.2015

Part number	Article designation	Version	For design	Pieces / PU
1mm contacts female				
74020601	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female slot 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	10
74200600	EPIC® M23 BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female slot 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	100
74034500	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (100)	1 mm female hyperboloid 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	100
2mm contacts female				
44429371	LS1 D BCEMF 2 mm AU 0.5 - 2.5 (10)	2 mm female spring 0,5-2,5mm ²	LS1 D6, A6	10
74034501	LS1 D BCEMS 1 mm AU 0.14 - 1.0 (10)	1 mm female hyperboloid 0.14 - 1.0 mm ²	per inserts M23 (not D-Sub), LS1 D6, A6	10
44429370	LS1 D BCEMF 2 mm AU 0.5 - 2.5 (100)	2 mm female spring 0,5-2,5mm ²	LS1 D6, A6	100
44420104	LS1 D BCEMD 2 mm AU 4,0 (10)	2 mm female hyperboloid 4 mm ²	LS1 D6	10
44420105	LS1 D BCEMD 2 mm AU 4,0 (100)	2 mm female hyperboloid 4 mm ²	LS1 D6	100
44429001	EPIC CIRCON BCBG 2MM 1.0-2.5 (3000) RE	2 mm female crimp	LS1 D6, A6	1

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	EPIC® POWER LS1 Contacts female	05.11.2015



Product Management	Document: LAPP_PRO136968EN.pdf	3 / 3
--------------------	--------------------------------	-------