

TMRJ-1 SURG-SS055M



Body Features

| | |
|-----------------|----------------------|
| Color | Gray |
| Cable Exit Type | Straight to straight |
| Ferrite Core | Without |
| Shield Material | Carbon steel |

Configuration Features

| | |
|---------------------------|--------------|
| Configuration | Double-ended |
| Keyed | No |
| Number of Positions | 24-pair |
| Number of Power Positions | 0 |

Dimensions

| | |
|--------------------------------|-------------------------------|
| Cable Assembly Length | 55000 mm |
| Length | 55.000 m 180.446 ft |
| Overall Outside Cable Diameter | 0.510 mm 0.020 in |
| Wire Size (CMA) | .205 mm ² 24 AWG |

Industry Standards

| | |
|---------------------|-----|
| Flammability Rating | CMR |
| IEEE 1394 | No |

Mechanical Attachment

| | |
|-----------|------|
| Jackscrew | With |
|-----------|------|

Operation/Application

| | |
|--------------|----|
| Halogen Free | No |
|--------------|----|

Product Availability

| | |
|--------|--------------------------------------|
| Region | Asia Latin America North America |
|--------|--------------------------------------|

Product Type Features

| | |
|-------------------------|-----------------------------|
| Product Type | Cable Assembly |
| System | MRJ21™ |
| Assembly Type | MRJ21™ (180) to MRJ21 (180) |
| Cable Assembly Category | High Speed |
| Cable Assembly Type | MRJ21™ |

TMRJ-1SURG-SS055M

| | |
|------------------------|--------------|
| Cable Style | CMR |
| Connector Type (End A) | Plug |
| Connector Type (End B) | Plug |
| Latching Style | Jackscrews |
| Performance Category | 1Gb Ethernet |
| Product Designation | Patch Cord |
| Shielded | Yes |

Signal Characteristics

| | |
|-----------|-----------|
| Data Rate | 1.00 Gb/s |
|-----------|-----------|

Usage Conditions

| | |
|-----------------------------|-------------|
| Operating Temperature Range | -10 – 60 °C |
|-----------------------------|-------------|

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant