


Metal Meleon Pro A: Galvanized Steel Smooth PVC Coating - IP 65

Part Numbers	DN Size	Dimensions in Inches (mm)			
		d		D	Roll Length (Ft.)
		Inner Diameter	Outer Diameter		
-4°F to 221°F (-20°C to 105°C)					
MP-1016-SPA	10	.41 (10.3)	.63 (16)	98	40
MP-1218-SPA	12	.48 (12.3)	.71 (18)	98	45
MP-1621-SPA	16	.61 (15.5)	.83 (21)	98	65
MP-2127-SPA	21	.82 (20.9)	1.04 (26.5)	98	100
MP-2733-SPA	27	1.04 (26.5)	1.31 (33.3)	98	135
MP-3542-SPA	35	1.38 (35)	1.65 (42)	49	175
MP-4048-SPA	40	1.57 (40)	1.90 (48.2)	49	230
MP-5160-SPA	51	2.03 (51.5)	2.36 (60)	49	280




RoHS




Metal Meleon Pro B: Galvanized Steel with Braid - IP 40

Part Numbers	DN Size	Dimensions in Inches (mm)			
		d		D	Roll Length (Ft.)
		Inner Diameter	Outer Diameter		
-148°F to 572°F (-100°C to 300°C)					
MP-0914-SPB	9	.35 (9)	.55 (14)	164	1.18 (30)
MP-1116-SPB	11	.43 (11)	.63 (16)	164	1.38 (35)
MP-1318-SPB	13	.51 (13)	.69 (17.5)	164	1.57 (40)
MP-1621-SPB	16	.63 (16)	.83 (21)	164	1.77 (45)
MP-2126-SPB	21	.83 (21)	1.02 (26)	164	2.17 (55)
MP-2632-SPB	26	1.02 (26)	1.26 (32)	82	2.76 (70)
MP-3541-SPB	35	1.38 (35)	1.61 (41)	82	3.15 (80)
MP-4046-SPB	40	1.57 (40)	1.81 (46)	82	3.54 (90)
MP-5157-SPB	51	2.01 (51)	2.24 (57)	82	3.51 (90)



RoHS




Extreme Temperatures

Metal Meleon Pro C: Galvanized Steel PVC Coating with Braid - IP 65

Part Numbers	DN Size	Dimensions in Inches (mm)			
		d		D	Roll Length (Ft.)
		Inner Diameter	Outer Diameter		
5°F to 158°F (-15°C to 70°C)					
MP-0915-SPC	9	.35 (9)	.55 (14)	164	1.18 (30)
MP-1117-SPC	11	.43 (11)	.63 (16)	164	1.38 (35)
MP-1319-SPC	13	.51 (13)	.69 (17.5)	164	1.57 (40)
MP-1622-SPC	16	.63 (16)	.83 (21)	164	1.77 (45)
MP-2127-SPC	21	.83 (21)	1.02 (26)	164	2.17 (55)
MP-2633-SPC	26	1.02 (26)	1.26 (32)	82	2.76 (70)
MP-3542-SPC	35	1.38 (35)	1.61 (41)	82	3.15 (80)
MP-4047-SPC	40	1.57 (40)	1.81 (46)	82	3.54 (90)
MP-5158-SPC	51	2.01 (51)	2.24 (57)	82	3.54 (90)

RoHS



Optional Locking Nuts, O-Rings & Other Accessories starting on Page 29 - 40.