

## Shielded Multi-Conductor FT-4



1-888-Electro  
Fax 613-394-4101  
SALES@ELECTROCABLES.COM

Stranded Tinned Copper Conductors\*  
SR-PVC Insulation, 100% Aluminum Foil Shield  
Stranded Tinned Copper Drain, Grey PVC Jacket FT-4  
-20° C to 105° C, Contact [sales@electrocables.com](mailto:sales@electrocables.com) for approval info

[Home](#)  
[Electronic & Electrical Index](#)  
[Search](#)  
[Previous](#) [Next](#)  
[Colour Code: ECI Chart 2](#)

ECI Catalogue Number	Conductor			Drain AWG Size	Wall Thickness		Nominal O.D. (inches)	Total Weight (lbs/km)	Colour Code
	No.	Size	Stranding		Insulation (inches)	Jacket (inches)			
<b>5152209TFT4</b>	9	22	7 x 30	24	.010	.023	.227	153	<a href="#">ECI Chart 1</a>
<b>5152210TFT4</b>	10	22	7 x 30	24	.010	.023	.236	167	1
<b>5152211TFT4</b>	11	22	7 x 30	24	.010	.023	.239	169	1
<b>5152212TFT4</b>	12	22	7 x 30	24	.010	.023	.253	187	1
<b>5152215TFT4</b>	15	22	7 x 30	24	.010	.023	.277	233	2
<b>5152219TFT4</b>	19	22	7 x 30	24	.010	.030	.319	287	2
<b>5152220TFT4</b>	20	22	7 x 30	24	.010	.030	.325	287	2
<b>5152225TFT4</b>	25	22	7 x 30	24	.010	.030	.356	367	2
<b>5152230TFT4</b>	30	22	7 x 30	24	.010	.030	.383	420	2
<b>5152240TFT4</b>	40	22	7 x 30	24	.010	.030	.434	547	2
<b>5152250TFT4</b>	50	22	7 x 30	24	.010	.035	.487	649	2
<b>5152051TFT4</b>	2	20	7 x 28	22	.010	.020	.162	67	Black/Red
<b>5152003TFT4</b>	3	20	7 x 28	22	.010	.023	.176	93	ECI Chart 1
<b>5152004TFT4</b>	4	20	7 x 28	22	.010	.023	.191	113	1
<b>5152005TFT4</b>	5	20	7 x 28	22	.010	.023	.199	127	ECI Chart 2
<b>5152006TFT4</b>	6	20	7 x 28	22	.010	.023	.217	141	2
<b>5152007TFT4</b>	7	20	7 x 28	22	.010	.023	.232	167	2
<b>5152008TFT4</b>	8	20	7 x 28	22	.010	.023	.243	177	2
<b>5152009TFT4</b>	9	20	7 x 28	22	.010	.023	.255	195	2
<b>5152010TFT4</b>	10	20	7 x 28	22	.010	.023	.266	212	2
<b>5152012TFT4</b>	12	20	7 x 28	22	.010	.023	.287	247	2
<b>5152015TFT4</b>	15	20	7 x 28	22	.010	.030	.322	307	2

\*Stranded **bare** copper conductors and special packaging and colours available upon request.  
**Aluminum** or **Steel Interlock Armour** and Jacket available upon request.

The above data values are subject to change, please contact Electro Cables at [sales@electrocables.com](mailto:sales@electrocables.com) for verification of the above numbers to current manufacturing data values for your requirements or order.

This web site was last modified on Nov 27, 2015 , QMS registered to ISO 9001, Rev.60 All Rights Reserved.