

**Integrated Power Inlets and Outlets with Weather-Resistant Covers**

**Features and Benefits**

- Engineered to IP64 and NEMA 3R Protection Ratings
- Suitable for industrial indoor and outdoor use
- Glass-filled thermoplastic cover and plate provide outstanding impact resistance and durability
- UL 94 VO Flammability Rating
- IP64 Suitability Rating protects against dust particles and splashing water
- NEMA Type-3R Enclosure Rating ensures protection against rain, sleet and damage from external ice formations
- Available with standard wire wells or with slots that accept fork terminals
- Dual gaskets, one under plate and one under lid, for weather-resistant fit
- Stainless steel external hardware resists corrosive effects of moisture
- Large thumb-tab makes it easy to open cover with gloved hand
- Mounts to panels or FS/FD boxes
- UL Listed and CSA Certified for wet locations with cover closed

**15A 2-Pole, 3-Wire, Grounding**

| Rating                   | 15A-125V                  | 15A-125V                   |
|--------------------------|---------------------------|----------------------------|
| NEMA                     |                           |                            |
|                          | 5-15P                     | 5-15R                      |
| Description              | Cat. No.<br>Flanged Inlet | Cat. No.<br>Flanged Outlet |
| Standard Wire Wells      | <a href="#">5278-CWP</a>  | <a href="#">5279-CWP</a>   |
| Slots for Fork Terminals | <a href="#">5278-FWP</a>  | <a href="#">5279-FWP</a>   |



5278-CWP

**20A 2-Pole, 3-Wire, Grounding**

| Rating              | 20A-125V                  | 20A-125V                   | 20A-250V                  | 20A-250V                   |
|---------------------|---------------------------|----------------------------|---------------------------|----------------------------|
| NEMA                |                           |                            |                           |                            |
|                     | 5-20P                     | 5-20R                      | 6-20P                     | 6-20R                      |
| Description         | Cat. No.<br>Flanged Inlet | Cat. No.<br>Flanged Outlet | Cat. No.<br>Flanged Inlet | Cat. No.<br>Flanged Outlet |
| Standard Wire Wells | <a href="#">15378-CWP</a> | —                          | <a href="#">5478-CWP</a>  | <a href="#">5479-CWP</a>   |



15378-CWP

**SPOTLIGHT**

**Industrial Devices**

For over 107 years, Leviton has been helping businesses power their equipment safely, reliably, and efficiently. The Leviton line of rugged industrial electrical products comprises devices rated up to 1100A at 1000V, and includes devices with watertight and dust-tight ratings. For more information on Industrial devices visit us online at [www.leviton.com/industrial](http://www.leviton.com/industrial)

