

SKINTOP® GMP-GL-M

SKINTOP® GMP-GL-M, glass fibre-reinforced counter nuts, for maximum mechanical stability, for locking in boreholes without thread



Variety of approval certifications



UV-resistant



Temperature-resistant



Oil-resistant



Assembly time



Good chemical resistance

Benefits

Glass fibre-reinforced for maximum mechanical stability

Supporting surface for spanner means scratches on the housing are avoided

Application range

For locking SKINTOP® cable glands in boreholes without thread.

Norm references / Approvals

UL File Nr. E79903

SKINTOP® GMP-GL-M

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Note

UL approval only when used with the UL-approved SKINTOP® polyamide cable glands
Designed for use with metric SKINTOP® plastic cable glands

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000441 ETIM 5.0 Class-Description: Cable screw gland
On request:	Available without collar (without surface for assembling tool)
Colour delivered:	Silver grey (RAL 7001) Light grey (RAL 7035) Black (RAL 9005), UV-resistant
Material:	Polyamide, glass fibre-reinforced
Temperature range:	Fixed: -40°C to +100°C Dynamic: -20°C to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINTOP® GMP-GL-M**

Article number	Article designation / size	SW mm
SKINTOP® GMP-GL-M silver grey		
53119000	M 12 x 1,5	17
53119010	M 16 x 1,5	22
53119020	M 20 x 1,5	27
53119030	M 25 x 1,5	34
53119040	M 32 x 1,5	41
53119050	M 40 x 1,5	50
53119060	M 50 x 1,5	60
53119070	M 63 x 1,5	75
SKINTOP® GMP-GL-M black		
53119100	M 12 x 1,5	17
53119110	M 16 x 1,5	22
53119120	M 20 x 1,5	27
53119130	M 25 x 1,5	34
53119140	M 32 x 1,5	41
53119150	M 40 x 1,5	50
53119160	M 50 x 1,5	60
53119170	M 63 x 1,5	75
SKINTOP® GMP-GL-M light grey		
53119003	M 12 x 1,5	17
53119013	M 16 x 1,5	22
53119023	M 20 x 1,5	27
53119033	M 25 x 1,5	34
53119043	M 32 x 1,5	41
53119053	M 40 x 1,5	50
53119063	M 50 x 1,5	60
53119073	M 63 x 1,5	75

Last Update (21.06.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16