

Part Number: 5500F1

Security & Sound, #22-2c, TC, Shielded, CM, Water-Blocked



Product Description

Security & Sound Cable, Rated-CM, 2-22 AWG stranded tinned copper conductors with PVC insulation, waterblocking tape, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 22 | 7x30 | TC - Tinned Copper | 2 |

| | |
|------------------|--------|
| Conductor Count: | 2 |
| Conductor Size: | 22 AWG |

Insulation

| Material | Nominal Wall Thickness |
|--------------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.01 in |

Color Chart

| Number | Color |
|--------|-------|
| 1 | Black |
| 2 | Red |

Outer Shield Material

| Type | Material | Material Trade Name | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|------------------------------|---------------------|--------------|--------------------|---------------|------------------------------|
| Tape | Aluminum Foil-Polyester Tape | Beldfoil® | 100 % | TC - Tinned Copper | 24 | solid |

| | |
|-------|------------------------------|
| Note: | Non-woven waterblocking tape |
|-------|------------------------------|

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness | Ripcord |
|--------------------------|------------------|------------------------|---------|
| PVC - Polyvinyl Chloride | 0.196 in | 0.025 in | Yes |

Construction and Dimensions

Cabling

| Lay Length |
|------------|
| 1.5 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Conductor DCR | Conductor Resistance | Nominal Outer Shield DCR |
|-----------------------|-----------------------|----------------------|--------------------------|
| 16.1 Ohm/1000ft | 16.1 Ohm/1000ft | | 16.8 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
| 46 pF/ft | 82.8 pF/ft |

| | |
|------------|---------------------------|
| Shielding: | Foil(s) or Copper Tape(s) |
|------------|---------------------------|

Current

Max. Recommended Current [A]

Per conductor @ 25°C: 2.8 A

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

Operating Temp Range: -20°C To +105°C

Mechanical Characteristics

| | |
|----------------------------------|-----------------|
| Bulk Cable Weight: | 15.7 lbs/1000ft |
| Max Recommended Pulling Tension: | 23.7 lbs |
| Min Bend Radius/Minor Axis: | 2 in |

Standards

| | |
|--------------------------|-----|
| NEC Articles: | 800 |
| NEC/(UL) Specification: | CM |
| CEC/C(UL) Specification: | CM |
| CPR Euroclass: | Eca |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | Yes |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-10-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |

Flammability, LS0H, Toxicity Testing

| | |
|-------------------|-------------------|
| UL Flammability: | UL1685 UL Loading |
| CSA Flammability: | FT1 |

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

| Item # | Color | Footnote |
|----------------|-------|----------|
| 5500F1 0101000 | Black | |
| 5500F1 0081000 | Gray | C |

Footnote: C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief.

at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.