

553-50089

Article Number: 553-50089



Description: Heat Shrink Label, .25" 3-Slit Single Sided, Polyolefin, White, 4000/BX

Base Data	Local Order Number	553-50089
	Type	HST6-2WH-3S
	Color	White (WH)
	Features and Benefits	<ul style="list-style-type: none"> • Slide Slit and optional center slits for easy wire insertion. • Smooth surface for clean and legible printing. • Supplied on a ladder style carrier so that markers can be kitted after printing. • A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
	Quantity Per	box
	Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.
	Short Description	Heat Shrink Label, .25" 3-Slit Single Sided, Polyolefin, White, 4000/BX
	Product Dimensions	Length L (Imperial)
Length L (Metric)		10.67mm
Printable (Yes/No)		Yes
Variant		Thin-Wall
Width W (Imperial)		0.475"
Width W (Metric)		12mm
Height H (Imperial)		0.42"
Height H (Metric)		10.67mm
Diameter Max. (Imperial)		.25"
Outside Diameter Max. (Imperial)		0.25"
Outside Diameter Max. (Metric)		6.35mm
Wall Thickness WT (Imperial)		0.028"
Wall Thickness WT (Metric)		0.71mm

553-50089



Product Dimensions	Flexibility	Flexible
	Print Method	Thermal Transfer
	Recovered Diameter d (metric)	2.2mm
	Recovered Diameter d (imperial)	0.083"
	Supplied Diameter D (imperial)	0.236"
	Supplied Diameter D (metric)	6.0mm
	Thickness T (Metric)	3.0µm
	Width of Liner WL (metric)	76.2mm
	Width of Liner WL (imperial)	3.0
	Width of Printable Area (imperial)	.475
	Width of printable area (metric)	12.07mm
Material and Specifications		
	Material	Polyolefin, cross-linked (PO-X)
	Material Shortcut	PO-X
	US MILSPEC	SAE-AS81531
	Dielectric Strength (Metric)	19.7 kV min.
	Flammability	UL224 VW-1
	Shrink Temperature	+194 °F (+90 °C)
	Operating Temperature	-67°F to +275°F (-55°C to +135°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Certification/Specification	SAE - AS81531	
Logistic and Packaging		
	Package Quantity (Imperial)	4000
	Package Quantity (Metric)	4000
	Customs Number(Schedule B)	3926909987
	Markers per row	4
	Weight (Metric)	0.793kg
	Weight (imperial)	1.73