

553-50209

Article Number: 553-50209

Heat Shrink Label, 1.5" Unslit, Single Sided, Polyolefin, White 150/BX

HellermannTyton



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 553-50209

**Type** HST39-13WH

**Color** White (WH)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
  - Smooth surface for clean and legible printing.
  - Supplied on a ladder style carrier so that markers can be kitted after printing.
  - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

**Printable (Yes/No)** Yes

**Variant** Thin-Wall

**Short Description** Heat Shrink Label, 1.5" Unslit, Single Sided, Polyolefin, White 150/BX

## Product Dimensions

**Length L (Imperial)** 1.90 "

**Length L (Metric)** 48.3 mm

**Width W (Imperial)** 1.90 "

**Width W (Metric)** 48 mm

**Height H (Imperial)** 2.26 "

**Height H (Metric)** 57.4 mm

**Diameter Min. (Imperial)** 0.51 "

**Diameter Max. (Imperial)** 1.5 "

**Outside Diameter Max. (Imperial)** 1.5 "

**Outside Diameter Max. (Metric)** 38.1 mm

**Wall Thickness WT (Imperial)** 0.024 "

**Wall Thickness WT (Metric)** 1.2 mm

**Print Method** Thermal Transfer

**Recovered Diameter D (metric)** 13 mm

**Recovered Diameter D (imperial)** 0.51 "

**Supplied Diameter D (metric)** 38.1 mm

**Supplied Diameter D (imperial)** 1.5 "

**Thickness T (Metric)** 3.0  $\mu$ m

Width of Liner WL (metric) 76.2 mm  
Width of Liner WL (imperial) 3.0 "

## Logistics and Packaging

---

Quantity Per box  
Package Quantity (Imperial) 150  
Package Quantity (Metric) 150  
Markers per row 1  
Weight (imperial) 1.48 lbs  
Weight (Metric) 0.68 kg

## Material and Specifications

---

Material Polyolefin, cross-linked (PO-X)  
Material Shortcut PO-X  
Abrasion Resistance Good  
Dielectric Strength (metric) 19.7 kV min.  
Flammability UL224 VW-1  
Shrink Temperature +194 °F (+90 °C)  
Operating Temperature -67°F to +275°F (-55°C to +135°C)  
Recommended Ribbon Type TTDTHOUT  
TTRC+  
ROHS compliant (Article 4 - 1) Yes  
Certification/Specification MIL-STD-202G Method 215K  
UL224 125 °C 600V VW-1  
SAE - AMS - DTL-23053/5 Class 1 and 3  
SAE-AS81531