

558-00056

Article Number: 558-00056

SwiftMark Self-Laminating Label, 1.5" X 1.0" X 3.0", Vinyl, White, 1000/RL



Download spec sheet

## Base Data

**Local Order Number** 558-00056

**Type** TAG85-100W381SM

**Color** White (WH)

- Features and Benefits**
- HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.
  - Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
  - Labels are UL recognized for indoor and outdoor use to expand application options.
  - HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.

**Color Marking Field** White (WH)

**Product Description** HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

**Mounting method Identification ETIM** Pasting / Stick

**Short Description** SwiftMark Self-Laminating Label, 1.5" X 1.0" X 3.0", Vinyl, White, 1000/RL

## Product Dimensions

**Variant** Roller form

**Width W (Imperial)** 1.5 "

**Width W (Metric)** 38.1 mm

**Height H (Imperial)** 1.0 "

**Height H (Metric)** 25.4 mm

**Height H2 (Imperial)** 3.0 "

**Height H2 (Metric)** 76.2 mm

**Bundle Diameter Min. (Imperial)** 0.39 "

**Bundle Diameter Min. (Metric)** 10.1 mm

**Bundle Diameter Max. (Imperial)** 0.7 "

**Bundle Diameter Max. (Metric)** 17.70 mm

**Outside Diameter Min. (Imperial)** 0.79 "

**Outside Diameter Min. (Metric)** 10.1 mm

**Outside Diameter Max. (Imperial)** 0.39 "

<b>Outside Diameter Max. (Metric)</b>	20.2 mm
<b>Horizontal Repeat HR (imperial)</b>	1.5 "
<b>Horizontal Repeat HR (metric)</b>	38.1 mm
<b>Print Method</b>	Thermal Transfer
<b>Thickness T (Metric)</b>	35 µm
<b>Vertical Repeat VR (metric)</b>	82.55 mm
<b>Vertical Repeat VR (imperial)</b>	3.25 "
<b>Width of Liner WL (imperial)</b>	1.625 "
<b>Width of Liner WL (metric)</b>	41.27 mm

---

## Logistics and Packaging

<b>Quantity Per</b>	reel
<b>Package Quantity</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Carton Quantity</b>	1000
<b>Labels per Row</b>	1
<b>Weight (imperial)</b>	2.08
<b>Weight (Metric)</b>	0.94 kg

---

## Material and Specifications

<b>Material</b>	Type 100, Vinyl (PVC), white (WH), self laminating
<b>Material Shortcut</b>	100B
<b>Adhesive</b>	Acrylic
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized