

558-00058

Article Number: 558-00058

SwiftMark Self-Laminating Label, 2.0" X 1.0" X 3.0", Vinyl, White, 1000/RL

HellermannTyton



Download spec sheet

Base Data

Local Order Number 558-00058

Type TAG85-100W508SM

Color White (WH)

Features and Benefits

- HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.
- Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.
- Labels are UL recognized for indoor and outdoor use to expand application options.
- HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.

Color Marking Field White (WH)

Product Description HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

Mounting method Identification ETIM Pasting / Stick

Variant Roller form

Short Description SwiftMark Self-Laminating Label, 2.0" X 1.0" X 3.0", Vinyl, White, 1000/RL

With label space ETIM Yes

Product Dimensions

Core diameter from / to 10.1 - 20.2 mm

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Height H (Imperial) 1.0 "

Height H (Metric) 25.4 mm

Height H2 (Imperial) 3.0 "

Height H2 (Metric) 76.2 mm

Bundle Diameter Min. (Imperial) 0.39 "

Bundle Diameter Min. (Metric) 10.1 mm

Bundle Diameter Max. (Imperial) 0.7 "

Bundle Diameter Max. (Metric) 17.70 mm

Outside Diameter Min. (Imperial) 0.79 "

Outside Diameter Min. (Metric)	10.1 mm
Outside Diameter Max. (Imperial)	0.39 "
Outside Diameter Max. (Metric)	20.2 mm
Horizontal Repeat HR (imperial)	2.0 "
Horizontal Repeat HR (metric)	50.8 mm
Print Method	Thermal Transfer
Thickness T (Metric)	35 µm
Thickness of Foil (TF)	35 µm
Vertical Repeat VR (metric)	82.55 mm
Vertical Repeat VR (imperial)	3.25 "
Width of Liner WL (imperial)	2.125 "
Width of Liner WL (metric)	53.97 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Carton Quantity	1000
Labels per Row	1
Weight (Metric)	1.2 kg
Weight (imperial)	2.65

Material and Specifications

Material	Type 100, Vinyl (PVC), white (WH), self laminating
Material Shortcut	100B
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Operating Temperature	-40°F to +176°F (-40°C to +80°C)
ROHS compliant (Article 4 - 1)	Yes
Certification/Specification	UL-Recognized