




UL 3271 / CSA AWM I A/B 125°C 600V RADOX connecting leads

GENERAL PROPERTIES:

Excellent high temperature, low temperature, ozone and weathering resistance, flame retardant, easy to strip and process, heat pressure and highly abrasion resistant, soldering iron resistant, flexible.

APPLICATION:

For protected and fixed installation inside electrical equipment, especially suitable for the connection of motor windings, switchboards, magnets and transformers.



1. Conductor : Stranded tin plated copper, flexible
 2. Coverage : Tape (\geq 6AWG only)
 3. Insulation : RADOX
extruded irradiation crosslinked polyolefin
- Colours : various

Printing:

\leq 10 mm²

AWM Style 3271 125 °C 600V HUBER + SUHNER [prod.-place] RADOX CSA AWM I A/B 125 °C 600V FT2 [cross section]

\geq 16 mm²

AWM Style 3271 125 °C 600V HUBER + SUHNER [prod.-place] RADOX CSA AWM I A/B 125 °C 600V FT1, FT2 [cross section]

Technical data:

Voltage rating	(UL/CSA)	600	V
Testvoltage 1 min.	(UL/CSA)	2500	V
Voltage rating	(\geq 0.5mm ²)	600/1000	V
Testvoltage 1 min.	(\geq 0.5mm ²)	3500	V
Temperature rating	(UL/CSA)	+ 125	°C
Max. Temperature at short circuit	(max. 5s)	+ 280	°C
Min. temperature	flexing	- 25	°C
	fixed	- 40	°C
Min. bending radius for fixed installation		see Tab. 1	

The cables comply with the following standards:

Appliance wiring material	CSA C22.2 No. 210	AWM I A/B 125°C 600 V
Appliance wiring material	UL 758	Style 3271

The cables pass the following fire tests:

Vertical flame spread FT1	(\geq 16mm ²)	L \leq 250 mm, t \leq 60 s ...	CSA C22.2 No. 2556 # 9.3
Horizontal flame spread FT2		L \leq 100 mm	CSA C22.2 No. 2556 # 9.1
Vertical flame spread		50 < L \leq 540 mm	EN 60332-1-2, IEC 60332-1-2
Horizontal flame spread, Appliance-Wire		V \leq 25 mm/min.	UL 1581 # 1090

Copyright 2017 HUBER+SUHNER AG. This document may not be amended and its content is confidential. It may not be passed on to third party which are not bound by confidentiality.

The product fulfils the test and specification requirements described in this document for the stated areas of application and operating conditions. HUBER+SUHNER AG does not expressly or implicitly guarantee performance under additional or changed conditions. Deviations are to be agreed upon in writing.

HUBER+SUHNER AG Low Frequency Division

CH-8330 Pfäffikon



+41 (0)44 952 22 11



+41 (0)44 952 26 40

www.hubersuhner.com



UL 3271 / CSA AWM I A/B 125°C 600V RADOX connecting leads

Approvals:

UL
CSA

File E63322
File 069581

TABLE 1: Dimensions, weight

Cross Section: UL 758 CSA C22.2 No. 210		Cross-section: EN 60228/ IEC 60228 nom. mm2	Conductor construction nom. n x mm d	Conductor diameter		Core diameter D. mm	Weight nom. kg / 100m	Bending radius min. mm	Conductor resistance at 20°C max. Ω / km
AWG	nom. mm2			max. mm					
24	0.205		19 x 0.13	0.61	2.22 ± 0.10	0.72	3 x D	86.0	
22	0.324		19 x 0.16	0.77	2.40 ± 0.10	0.92	3 x D	53.1	
		0.5	19 x 0.18	0.90	2.55 ± 0.10	1.0	3 x D	38.2	
20	0.519		19 x 0.20	0.99	2.60 ± 0.10	1.2	3 x D	32.4	
		0.75	24 x 0.20	1.13	2.80 ± 0.10	1.3	3 x D	26.7	
18	0.823		19 x 0.25	1.23	2.85 ± 0.10	1.6	3 x D	20.4	
		1	32 x 0.20	1.28	2.95 ± 0.10	1.6	3 x D	20.0	
(16)		1.5	19 x 0.31	1.52	3.20 ± 0.10	2.1	3 x D	13.0	
14	2.08		19 x 0.37	1.86	3.50 ± 0.10	2.9	3 x D	9.32	
		2.5	48 x 0.25	2.06	3.75 ± 0.10	3.2	3 x D	8.21	
12	3.31		37 x 0.35	2.35	4.00 ± 0.15	4.2	3 x D	5.88	
		4	56 x 0.30	2.64	4.35 ± 0.15	4.9	3 x D	5.09	
10	5.26		37 x 0.44	3.02	4.70 ± 0.15	6.4	3 x D	3.62	
		6	84 x 0.30	2.98	4.70 ± 0.15	6.9	3 x D	3.23	
(8)		10	80 x 0.40	3.94	6.40 ± 0.15	12.1	3 x D	1.95	
(6)		16	119 x 0.40	5.4	8.60 ± 0.2	18.8	3 x D	1.24	
(4)		25	182 x 0.40	6.7	9.90 ± 0.2	26.8	3 x D	0.795	
(2)		35	266 x 0.40	7.9	11.1 ± 0.2	36.4	3 x D	0.565	
(1)		50	378 x 0.40	9.4	13.7 ± 0.25	54.3	4 x D	0.393	
(2/0)		70	348 x 0.49	11.5	15.8 ± 0.25	70.1	4 x D	0.273	
(3/0)		95	456 x 0.49	13.0	17.5 ± 0.3	90.2	4 x D	0.207	
(4/0)		120	570 x 0.50	14.7	19.6 ± 0.3	114	4 x D	0.164	
(250kcmil)		150	722 x 0.49	16.2	20.9 ± 0.3	139	4 x D	0.132	