



# RADOX® 155


## Connecting leads

### GENERAL PROPERTIES :

Excellent high temperature, low temperature, ozone and weathering resistance, flame retardant, soldering iron resistant, easy to strip and process, compatible to all common resins and varnishes, flexible.

### APPLICATION :

For protected and fixed installation inside electrical equipment, especially suitable for the connection of motor windings, switchboards, magnets and transformers.



1. Conductor : Stranded tin plated copper, class 5 EN 60228
2. Insulation : . RADOX 155,  
..... extruded irradiation crosslinked polyolefin  
Colours : ... diverse

### PRINTING :

0.25- 4 mm<sup>2</sup>:  
≥ 6 mm<sup>2</sup>:

HUBER+SUHNER RADOX 155 ...MM2 [prod.- place]  
HUBER+SUHNER [Lot No.] RADOX 155 ...MM2 [prod.- place]

### TECHNICAL DATA:

Temperature range ..... - 55 ... + 155 ..... °C

#### Voltages for cross-section ≥ 0.75 mm<sup>2</sup>:

Rated voltage cond.- earth	U <sub>0</sub>	600 V AC
Rated voltage cond.- cond.	U	1000 V AC
Maximum permitted operating voltage cond.- earth		720 V AC
Maximum permitted operating voltage cond.- cond.	U <sub>m</sub>	1200 V AC
Maximum permitted operating voltage cond.- earth	V <sub>0</sub>	900 V DC
Maximum permitted operating voltage cond.- cond.		1800 V DC
Test voltage		3500 V AC

#### Voltages for cross-section < 0.75 mm<sup>2</sup>:

Rated voltage cond.- earth	U <sub>0</sub>	450 V AC
Rated voltage cond.- cond.	U	750 V AC
Maximum permitted operating voltage cond.- earth		480 V AC
Maximum permitted operating voltage cond.- cond.	U <sub>m</sub>	825 V AC
Maximum permitted operating voltage cond.- earth	V <sub>0</sub>	620 V DC
Maximum permitted operating voltage cond.- cond.		1240 V DC
Test voltage		2500 V AC

Minimum bending radius ..... Outer diameter ≤ 12 mm ..... 3 x D  
..... Outer diameter > 12 mm ..... 4 x D

Copyright 2017 Huber + Suhner AG. This document may not be amended and its content is confidential. It may not be passed on to third party which are not bound by confidentiality.

The product fulfils the test and specification requirements described in this document for the stated areas of application and operating conditions. HUBER+SUHNER AG does not expressly or implicitly guarantee performance under additional or changed conditions. Deviations are to be agreed upon in writing.

**HUBER+SUHNER**  
**Low Frequency Division**

CH- 8330 Pfäffikon



+41 (0)44 952 22 11



+41 (0)44 952 26 40

www.hubersuhner.com



# RADOX® 155

## Connecting leads

TABLE 1 : Dimensions, conductor resistance, weight

Cross-section EN 60228 nom. mm <sup>2</sup>	Conductor construction nom. n x mm d	Conductor diameter max. mm	Core diameter Dia. mm	Conductor resistance at 20°C max. Ω / km	Weight nom. kg / 100m
0.25	19 x 0.13	0.61	1.45 ± 0.05	86.0	0.4
0.34	19 x 0.16	0.77	1.60 ± 0.10	53.1	0.5
0.5	19 x 0.18	0.90	1.71 ± 0.10	40.1	0.7
0.75	24 x 0.20	1.13	2.25 ± 0.10	26.7	1.1
1	32 x 0.20	1.28	2.50 ± 0.10	20.0	1.5
1.5	30 x 0.25	1.52	2.85 ± 0.10	13.7	1.9
2.5	48 x 0.25	2.06	3.50 ± 0.10	8.21	3.0
4	56 x 0.30	2.64	4.20 ± 0.15	5.09	4.5
6	82 x 0.30	2.98	5.0 ± 0.15	3.39	6.5
10	78 x 0.40	3.94	6.4 ± 0.15	1.95	11
16	119 x 0.40	5.4	7.6 ± 0.15	1.24	16.5
25	182 x 0.40	6.7	9.2 ± 0.2	0.795	25
35	266 x 0.40	7.9	10.7 ± 0.3	0.565	36.3
50	378 x 0.40	9.4	12.4 ± 0.3	0.393	50
70	348 x 0.49	11.5	14.6 ± 0.3	0.273	67
95	456 x 0.49	13.0	16.4 ± 0.3	0.207	87
120	570 x 0.50	14.7	18.5 ± 0.3	0.164	110
150	722 x 0.49	16.2	20.8 ± 0.3	0.132	139
185	874 x 0.50	18.0	22.7 ± 0.3	0.108	169
240	1147 x 0.50	21.0	26.1 ± 0.4	0.0817	219