



PRODUCT DATA SHEET

Group Number:	5616
Description:	16 19/0.0110" BC 0.023" PVC SAE J1128 GPT Ford ESF-M1L56-A, ESB-M1L58-A Chrysler MS-3450
Nominal OD:	0.102" +/- 0.005"
Nominal Wall:	0.023"
Copper Conductor:	16 19/0.0110 BC 1.5" Left Hand Lay
Insulation:	PVC
Temperature Ratings:	J1128 GPT 80C TCR ESB-M1L56-A 85C ESB-M1L58-A 105C MS-3450 105C
Voltage Ratings:	J1128 60VDC 25VAC

ROHS Compliance:

DixieWire Company and our key suppliers support the European Union Directive 2002/95/EC (RoHS) that restricts the use of certain hazardous substances in the design and manufacture of Electrical and Electronic Equipment. We have investigated the materials used in the manufacture of our products for the presence of substances restricted by European Union Restriction of Hazardous Substance Directive, citation 2002/95/EC. The substances covered by this investigation and the limits used are:

Lead	0.1%
Mercury	0.1%
Cadmium	0.01%
Chromium VI	0.1%
Polybrominated biphenyls (PBB)	0.1%
Polybrominated diphenyl ethers (PBDE)	0.1%

For product manufactured on or after March 1, 2006, during manufacturing we do not use or intentionally incorporate into the product any of the above substances in amounts which exceed the applicable limits. Trace levels could be present as contaminants.