



Automotive cable, flexible

RADOX Elastomer S Battery Cable


General Properties:

Excellent resistance to high and low temperature, ozone, UV and weathering resistance, resistant to pressure at high temperature, motor oil, fuels and hydrolysis, flame retardant, high abrasion resistant, solder iron resistant, easy to strip and process, according to ISO 6722 class D.

Complies with EU- directive 2000/53/EG on end of life vehicles. It is free from lead, mercury, cadmium and chrome VI.

Application:

Low voltage cable, for use in road vehicle applications.



1. Conductor: Stranded bare copper, acc. ISO 6722
2. Coverage: Tape
3. Insulation: RADOX Elastomer S (REMS) extruded irradiation crosslinked copolymer
Colours: various

Printing on Sheath, for items with „PY“ in the description:
HUBER+SUHNER RADOX [part. No.]-[batch. No.] [prod. week-year]

Technical Data:

Voltage rating cond.- earth	U ₀	600	V AC
Voltage rating cond.- cond.	U	1'000	V AC
maximum permissible Voltage rating AC cond.- earth		720	V AC
maximum permissible Voltage rating AC cond.- cond.	U _m	1'200	V AC
maximum permissible Voltage rating DC cond.- earth	V ₀	900	V DC
maximum permissible Voltage rating DC cond.- cond.		1'500	V DC
Test voltage, 50 Hz, 1 min.		3.5	kV AC
		8.4	kV DC
Temperature range (3'000 h)		- 40 ... + 150	°C
Min. bending radius	fixed	3 x cable D	
	flexing	5 x cable D	

Cross-section nominal mm ²	Conductor				Cable		
	Number of individual wires Guide value	Diameter of individual wires max. mm	Diameter max. mm	Resistance at 20° C max. Ω/km	Wall thickness min. mm	Weight nom. kg/100 m	Diameter nom. mm
10	78	0.41	4.3	1.82	0.50	10.7	5.75 ± 0.15
12	92	0.41	4.65	1.52	0.50	12.1	6.05 ± 0.15
16	126	0.41	5.4	1.16	0.52	16.7	6.90 ± 0.20
20	154	0.41	6.2	0.955	0.52	20.2	7.60 ± 0.20
25	189	0.41	6.7	0.743	0.55	24.5	8.20 ± 0.20
30	224	0.41	7.4	0.647	0.64	29.9	9.10 ± 0.25
35	273	0.41	7.9	0.527	0.65	35.4	9.70 ± 0.25
50	385	0.41	9.4	0.368	0.80	49.8	11.50 ± 0.25
70	360	0.51	11.6	0.259	0.80	70.4	13.70 ± 0.25
95	480	0.51	13.5	0.196	0.90	95.0	16.25 ± 0.30
120	589	0.51	15.1	0.153	0.90	115.9	18.00 ± 0.30

Copyright 2017 Huber + Suhner AG. This document may not be copied nor be passed on to third parties without our written permission
Uncontrolled copy when printed [will not be updated].

The product fulfils the test and specification requirements described in this document for the stated areas of application and operating conditions. HUBER+SUHNER AG does not expressly or implicitly guarantee performance under additional or changed conditions. Deviations are to be agreed upon in writing.

HUBER+SUHNER

Low Frequency Division

CH- 8330 Pfäffikon

+41 (0)44 952 22 11

+41 (0)44 952 26 40

www.hubersuhner.com