

4 3 2 1

| ITEM | COLOR | DIM "A" | DIM "B" | DIM "C" | DIM "D" | DIM "E" | DIM "F" | DIM "G" | DIM "H" | APPLICATION | "I" | "J" |
|------|-----------------------------|-----------------|-----------|-------------|-----------|------------|-----------|-------------|-----------------|--|-----|-----|
| H01 | WHITE | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB, GFEP 15-30A. | | |
| H02 | WHITE | 0.719 | .180 MAX | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB, GFEP 40-50A. | | |
| H03 | WHITE | | .220 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB, GFEP 60A. | | |
| H04 | BLACK | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB 15-30A. | | |
| H05 | BLACK | 0.719 | .180 MAX | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB 40-50A. | | |
| H06 | BLACK | | .220 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB, GFEP 60A. | | |
| H07 | WHITE | 0.500 | .163/150 | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 2 POLE 15-30A. | | |
| H08 | WHITE | 0.500 | .180 MAX | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 2 POLE 40A. | | |
| H09 | WHITE | 0.625 | .220 | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 2 POLE 50-60A. | | |
| H10 | BLACK | 0.500 | .163/150 | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 2 POLE 15-30A. | | |
| H11 | BLACK | 0.500 | .180 MAX | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 2 POLE 40A. | | |
| H12 | BLACK | 0.625 | .220 | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 2 POLE 50-60A. | | |
| H13 | WHITE | 0.700 | .220 | 0.250±.04 | | 24.00±.062 | 1.36±.030 | 1.00±.020 | * | 3/4" 2-P 35-60A | | |
| H14 | WHITE | 0.500 | .163/150 | 0.500 | 2.750 | 36.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 2 POLE 15-30 GFCB & GFEP | | |
| H15 | WHITE | 0.672 | .163/150 | 0.500 | 2.500 | 36.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 1 POLE 15-30 GFCB & GFEP | | |
| H16 | WHITE WITH BLUE STRIPE | 0.672 | .163/150 | 0.625 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 15A, 30mA | | |
| H17 | WHITE WITH BLACK STRIPE | 0.672 | .163/150 | 0.625 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 20A, 30mA | | |
| H18 | WHITE WITH 2 BLUE STRIPES | 0.672 | .163/150 | 0.625 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 15A, 5mA | | |
| H19 | WHITE WITH 2 BLACK STRIPES | 0.672 | .163/150 | 0.625 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 20A, 5mA | | |
| H20 | WHITE | 0.672 | .180 MAX | 0.500 | 2.500 | 36.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 1 POLE 30A. GFCB & GFEPXXXXT1 | | |
| H21 | WHITE WITH BLUE STRIPE | 0.312 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 20A 3/4" 30mA | | |
| H22 | WHITE WITH BLACK STRIPE | 0.312 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 15A 3/4" 30mA | | |
| H23 | WHITE WITH 2 BLUE STRIPES | 0.312 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 20A 3/4" 5mA | | |
| H24 | WHITE WITH 2 BLACK STRIPES | 0.312 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 15A 3/4" 5mA | | |
| H25 | WHITE WITH BLUE STRIPE | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 20A 1" 30mA | | |
| H26 | WHITE WITH BLACK STRIPE | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 15A 1" 30mA | | |
| H27 | WHITE WITH 2 BLUE STRIPES | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 20A 1" 5mA | | |
| H28 | WHITE WITH 2 BLACK STRIPES | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 15A 1" 5mA | | |
| H29 | WHITE WITH 2 ORANGE STRIPES | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 20A 1" 30mA FOR GE | | |
| H30 | WHITE WITH 1 ORANGE STRIPE | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AFD 15A 1" 30mA FOR GE | | |
| H31 | WHITE | 0.312 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 3/4" AFCI | | |
| H32 | GRAY | 0.672 | .163/150 | 0.500 | 2.500 | 48.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 1 POLE 15A QCGFEP | | |
| H33 | WHITE | 0.312 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | 1- POLE MARINE GFI | | |
| H34 | WHITE | 0.312 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | INTERIM AFD | | |
| H35 | WHITE | 0.672 | .163/150 | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB, GFEP 15-30A. | | |
| H36 | WHITE | 0.719 | .180 MAX | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFCB, GFEP 40-50A. | | |
| H37 | WHITE | 0.700 | .220 | 0.250±.04 | * | 18.00±.062 | 1.36±.030 | 1.00±.020 | * | 3/4" 2-P 35-60A. | | |
| H38 | WHITE | 0.220 | .163/150 | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | INTERIM AFD | | |
| H39 | WHITE | 0.672 | .163/150 | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | AF 15-20A | | |
| H40 | WHITE | 0.220 | .163/150 | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | INTERIM AFD 15-20A | | |
| H41 | WHITE | 0.108±0.010 | .163/150 | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | BR & CH TYPE SURGE BREAKER 30-50A | | |
| H42 | WHITE | 0.250 | .137±.003 | 0.875 | * | 4.150±.150 | 1.36±.030 | 1.00±.020 | * | BR CAF QUICK CONNECT. | | |
| H43 | WHITE | 0.250 | .137±.003 | 0.875 | * | 3.575±.062 | 1.36±.030 | 1.00±.020 | * | BR AFGF QUICK CONNECT. | | |
| H44 | WHITE | 0.719 | .180 MAX | 0.500 | 2.500 | 36.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFST 40-50A. | | |
| H45 | WHITE | 0.672 | .163/150 | 0.500 | 2.500 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFST 10-20A. | | |
| H46 | WHITE | 0.672 | .163/150 | 0.500 | 2.500 | 36.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | GFST 10-20A. | | |
| H47 | WHITE | 0.500 | .163/150 | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | BR AFGF ADV. 15-20A. | | |
| H48 | WHITE | 0.500 | .137±.003 | 0.875 | * | 4.150±.150 | 1.36±.030 | 1.00±.020 | * | BR AFGF ADV. 15-20A QUICK CONNECT. | | |
| H49 | WHITE | 0.500 | .163/150 | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | BR GF ADV. 30A. | | |
| H50 | GREEN | 0.500 | .200 MAX | 0.500 | 2.500 | 18.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | EV POLE EV-EMCB | | |
| H51 | WHITE | 0.220±0.040 | .137 | 0.625±0.080 | 3.00±.40 | 18.00±.062 | 1.36±.030 | 1.00±.020 | 2.00±.200 | EMCB WIFI POLE | | |
| H52 | WHITE | 0.500 | .130±.015 | 0.500 | | 18.33±.062 | 0.80±.030 | 1.00±.020 | .500MIN-.900MAX | BR AFG ADV. 15-20A. FOR BRAVOS IMPLEMENTATION - AUTOLINE | 5.5 | .90 |
| H53 | WHITE | 0.500 | .163/150 | 0.500 | | 18.33±.062 | 0.80±.030 | 1.00±.020 | .500MIN-.900MAX | BR GF ADV. 30A. FOR BRAVOS IMPLEMENTATION - AUTOLINE | 5.5 | .90 |
| H54 | WHITE | 0.250 | .130±.015 | 0.500 | | 18.00±.062 | 0.80±.030 | 1.00±.020 | .500MIN-.900MAX | INTERIM AFD 15-20A. FOR BRAVOS IMPLEMENTATION - AUTOLINE | 5.5 | .57 |
| H55 | WHITE | 0.217 ± 0.040 | .137 | 0.625±0.080 | 2.50±0.35 | 27.00±0.06 | 1.36±.030 | 0.900±0.080 | 1.55±0.35 | EMCB WIFI POLE | 9.5 | |
| H56 | WHITE | 0.217 ± 0.040 | .137 | 0.625±0.080 | 2.50±0.35 | 27.00±0.06 | 1.36±.030 | 0.900±0.080 | 1.55±0.35 | EMCB WIFI POLE (TINNED) | 9.5 | |
| H57 | WHITE | 0.350±.10/-0.00 | .163/150 | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | BRGF2P 15-30A | | |
| H58 | WHITE | 0.350±.10/-0.00 | .180 MAX | 0.500 | 2.750 | 24.00±.062 | 1.36±.030 | 1.00±.020 | .500MIN-.900MAX | BRGF2P 35-50A | | |
| H59 | WHITE | 0.220 | .163/150 | 0.500 | | 18.00±.062 | 0.80±.030 | 1.00±.020 | .500MIN-.900MAX | INTERIM AFD | 5.5 | .40 |
| H60 | WHITE | 0.220 | .130±.015 | 0.500 | | 18.00±.062 | 0.80±.030 | 1.00±.020 | .500MIN-.900MAX | INTERIM AFD 15-20A | 5.5 | .40 |

REFER TO ALTERNATE CONSTRUCTION IN SHEET 1.

| | | | | |
|--|---|---|--|--|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS IN INCHES X.X ±0.1 X.XX ±0.02 X.XXX ±0.005 X" ±1 X.X" ±.5 | DRAWING IN ACCORDANCE WITH ASME Y14.5M-1994 | DRAFTER/DESIGNER A. NUNEZ ENGINEERING APPROVED L. RENTERIA REVISION DESCRIPTION ECO# CO-0274938 | DATE (YYYYMMDD) 2023/12/14 MANUFACTURING M. GONZALEZ | EATON CORPORATION - CONFIDENTIAL AND PROPRIETARY NOTICE TO PERSONS RECEIVING THIS DOCUMENT AND/OR TECHNICAL INFORMATION THIS DOCUMENT, INCLUDING THE DRAWING AND INFORMATION CONTAINED THEREON, IS CONFIDENTIAL AND IS THE EXCLUSIVE PROPERTY OF EATON CORPORATION AND IS HEREBY ON LOAN AND SUBJECT TO RECALL BY EATON AT ANY TIME BY TAKING POSSESSION OF THIS DOCUMENT. THE RECIPIENT ACKNOWLEDGES AND AGREES THAT THIS DOCUMENT CANNOT BE USED IN ANY MANNER ADVERSE TO THE INTERESTS OF EATON AND THAT NO PORTION OF THIS DOCUMENT MAY BE COPIED OR OTHERWISE REPRODUCED WITHOUT THE PRIOR WRITTEN CONSENT OF EATON. IN THE CASE OF CONFLICTING CONTRACTUAL PROVISIONS, THIS NOTICE SHALL GOVERN THE STATUS OF THIS DOCUMENT. © 2014 Eaton Corporation. All Rights Reserved. |
| | CLASS CODE (S) ENGINFGR REFERENCE PRODUCT CODE: 3704 | TITLE QUICKLAG CIRCUIT BREAKER DETAIL FOR GROUND FAULT NEUTRAL LEADS | SIZE C | DRAWING NUMBER 5655B03 |
| CHANGE RESPONSIBILITY RWDD MCB ENGINEERING | | CLASS CODE NA | SCALE NTS | SHEET 2 OF 2 |

4 3 2 1