

595-22100

HellermannTyton

Article Number: 595-22100

Description: Dot Matrix Label, Self-Laminating, 1.0" x .50" x 1.43", 8 Across, White, 5000/pkg



Base Data	
Local Order Number	TAG22-100
Type	TAG22
Color	White (WH)
Features and benefits	<ul style="list-style-type: none"> • Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing. • Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.
Quantity Per	pack
Product Description	Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.
Global Part Name	TAG22-100-WH
Short Description	Dot Matrix Label, Self-Laminating, 1.0" x .50" x 1.43", 8 Across, White, 5000/pkg
Product Dimensions	
Length L (Imperial)	1.437"
Length L (Metric)	36.5mm
Self adhesive (Yes/No)	Yes
Variant	Adhesive label
Width W (Imperial)	1.0"
Width W (Metric)	25.4mm
Height H (Imperial)	.50"
Height H (Metric)	12.70mm
Height H2 (Imperial)	1.44"
Height H2 (Metric)	36.58mm
Height of printable area (metric)	12.70mm
Bundle Diameter Min. (Imperial)	.15"

595-22100



Product Dimensions	Bundle Diameter Min. (Metric)	3.80mm
	Bundle Diameter Max. (Imperial)	.29"
	Bundle Diameter Max. (Metric)	7.60mm
	Outside Diameter Min. (Imperial)	0.14"
	Outside Diameter Min. (Metric)	3.8mm
	Outside Diameter Max. (Imperial)	0.29"
	Outside Diameter Max. (Metric)	7.60mm
	Horizontal Repeat HR (metric)	12.70mm
	Horizontal Repeat HR (imperial)	.50"
	Print Method	Dot-Matrix
	Thickness T (Metric)	75.0µm
	Vertical Repeat VR (imperial)	1.5"
	Vertical Repeat VR (metric)	38.10mm
	Width of Liner WL (imperial)	8.9"
	Width of Liner WL (metric)	228.60mm
Material and Specifications		
	Material	Type 100, Vinyl (PVC), white (WH), self laminating
	Material Shortcut	100
	Adhesive	Acrylic
	Adhesive Operating Temperature	-51°F to +200°F (-46°C to +93°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-51°F to +200°F (-46°C to +93°C)
	ROHS Compliant	Yes
	Certification/Specification WEB	UL-Recognized
UL Recognized (US)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	5000
	Package Quantity (Metric)	5000
	Customs Number(Schedule B)	3919905060
	Labels per Column	8
	Labels per Row	8
	Weight (Metric)	0.08kg