

596-00232

Article Number: 596-00232



Pre-Printed Solar Label, "WARNING - ELECTRICAL SHOCK HAZARD W/DC", 3.75" X 2.5", Vinyl, Red, 50/RL



Download spec sheet

Base Data

Local Order Number	596-00232
Type	WESHLBLDC
Color	Red (RD)
Features and Benefits	<ul style="list-style-type: none"> • Made with UV stable inks and materials for durability and weather resistance. • The labels are supplied with aggressive adhesive to ensure long life. • Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	3.75" X 2.5" White text on red background that reads as: "WARNING - ELECTRICAL SHOCK HAZARD. DO NOT TOUCH TERMINALS. TERMINALS ON BOTH LINE AND LOAD SIDE MAY BE ENERGIZED IN THE OPEN POSITION. DC VOLTAGE IS ALWAYS PRESENT WHEN SOLAR MODULES ARE EXPOSED TO SUNLIGHT" - 50 per roll
Short Description	Pre-Printed Solar Label, "WARNING - ELECTRICAL SHOCK HAZARD W/DC", 3.75" X 2.5", Vinyl, Red, 50/RL

Product Dimensions

Width W (Imperial)	3.75 "
Width W (Metric)	95.25 mm
Height H (Imperial)	2.5 "
Height H (Metric)	63.5 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	50
Package Quantity (Metric)	50

Material and Specifications

Material	Type 443/552, UV Stable Flexible White Vinyl w/Acrylic Laminate
Material Shortcut	443/552
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Halogenfree	Yes
Operating Temperature	-40°F to +174°F (-40°C to +79°C)

ROHS Compliant Yes
Certification/Specification UL969
UL Recognized (US) Yes