

596-11822

# HellermannTyton

Article Number: 596-11822

Description: Thermal Transfer Label, .65" X .2", 4 Across, Polyester, White, 5000/RL



Base Data	Local Order Number	TAG11T4-822
	Type	TAG11T4
	Color	White (WH)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Thermal transfer labels are made with high performance materials for long term industrial applications.</li> <li>• Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.</li> <li>• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.</li> </ul>
	Quantity Per	reel
	Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
	Short Description	Thermal Transfer Label, .65" X .2", 4 Across, Polyester, White, 5000/RL
	Product Dimensions	Width W (Imperial)
Width W (Metric)		16.5mm
Height H (Imperial)		0.20"
Height H (Metric)		5.08mm
Horizontal Repeat HR (metric)		16.5mm
Horizontal Repeat HR (imperial)		0.65"
Print Method		Thermal Transfer
Vertical Repeat VR (imperial)		0.30"
Vertical Repeat VR (metric)		7.62mm
Width of Liner WL (metric)		66.04mm
Width of Liner WL (imperial)		2.60"

596-11822



Material and Specifications		
	Material	Type 822, Polyester, white (WH)
	Material Shortcut	822
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	5000
	Package Quantity (Metric)	5000
	Customs Number(Schedule B)	3919102055
	Labels per Row	4