



Floor Standing Cabinet Options



EIA/TIA Compliant

Spec. #
96-936
for full
product
info.

ABE



BS-MRK-31

Inner Platform Base [for MRK and WRK Series Racks]

Provides a handy platform, flush with bottom rackspace, for supporting heavy equipment and mounting electrical boxes. Fits inside rack.

Part #	Fits
BS-WRK-27	WRK 27" deep
BS-WRK-32	WRK 32" deep
BS-MRK-26	MRK 26" deep
BS-MRK-31	MRK 31" deep
BS-MRK-36	MRK 36" deep
BS-MRK-42	MRK 42" deep



component installation without inner platform base



component installation is simplified with inner platform base

BGR and EGR options are shown on rack series pgs.



5W
set of 4
commercial
grade casters

5WL
set of 4
commercial
locking
grade casters

5WR
set of 4
fine floor
casters

5WLR
set of 4
locking fine
floor casters

Swivel Casters [for ERK and Slim 5 Series Racks]

Bolt to bottom of all ERK & Slim 5 series rack systems. Adds 3-7/8" to overall height.

Commercial grade casters

- 1,300 lb. weight capacity

Fine floor casters

- 700 lb. weight capacity
- Constructed from synthetic rubber to protect fine flooring!

BGR and EGR options are shown on rack series pgs.



EIA/TIA Compliant

Spec. #
96-936
for full
product
info.

ABE



CBS-ERK-20R

Skirted Caster Bases [for ERK and Slim 5 Series Racks]

Skirted base hides wheels for an improved aesthetic appearance, and bolt to bottom of ERK and Slim 5 Series rack systems. Skirted caster bases add 3-3/4" to overall rack height. Each base comes with its wheels pre-installed.

Commercial grade casters

- Heavy duty non-locking 3" swivel wheels
- UL Listed in the US and Canada

Fine floor casters

- 700 lb. weight capacity
- Constructed from synthetic rubber to protect fine flooring!

Commercial Grade Caster Base Part #	Fine Floor Caster Base Part #	Fits
CBS-ERK-20	CBS-ERK-20R	ERK 20" deep
CBS-ERK-25	CBS-ERK-25R	ERK 25" deep
CBS-5	CBS-5R	Slim 5 20" deep
CBS-5-26	CBS-5-26R	Slim 5 26" deep

BGR and EGR options are shown on rack series pgs.



EIA/TIA Compliant

Spec. #
96-936
for full
product
info.

ABE



CBS-MRK-31

Recessed Caster Bases [for MRK, WRK and DRK Series Racks]

Recessed caster bases fit inside the rack and only increase the overall rack height by 15/16". Recessed Caster bases work with LF leveling feet, see pg. 31. Each base comes with its wheels pre-installed.

Commercial grade casters

- Heavy duty non-locking 3" swivel wheels
- 1,300 lb. weight capacity
- UL Listed in the US and Canada

Fine floor casters

- 700 lb. weight capacity
- Constructed from synthetic rubber to protect fine flooring!

Commercial Grade Caster Base Part #	Fine Floor Caster Base Part #	Fits
CBS-WRK-27	CBS-WRK-27R	WRK 27" deep
CBS-WRK-32	CBS-WRK-32R	WRK 32" deep
CBS-MRK-26	CBS-MRK-26R	MRK 26" deep
CBS-MRK-31	CBS-MRK-31R	MRK 31" deep
CBS-MRK-36	CBS-MRK-36R	MRK 36" deep
CBS-DRK-31	—	DRK 31" deep
CBS-DRK-36	—	DRK 36" deep





Casters (add 3-7/8" to overall cabinet height)

5W	5WR	5WL	5WLR	CBS-5	CBS-5R
set of 4 commercial grade casters	set of 4 fine floor casters	set of 4 commercial grade locking casters	set of 4 fine floor locking casters	skirted base with 4 commercial grade non-locking casters, fits 20" depth models; CBS-5-26 fits 26" depth models	skirted base with 4 fine floor non-locking casters, fits 20" depth models; CBS-5-26R fits 26" depth models


Accessories

SH-5A	Trim Panels	Adjustable "Split" Rear Rackrail	Top Fan & RAP Kit	Bottom Runner Kit														
zero space full depth front and rear mount SH Series rackshelf, see pg. 157	<table border="1"> <thead> <tr> <th>Part #</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>5-BAVTRIM</td> <td>black brushed & anodized</td> </tr> </tbody> </table> <p>top and bottom trim panels available to match the finish of the products mounted within the enclosures, includes 2 pieces</p>	Part #	Description	5-BAVTRIM	black brushed & anodized	<ul style="list-style-type: none"> Facilitates rear hanging of equipment Permits panels to be "mid-mounted" All brackets, rails and hardware included Cable chase kit required when using this option with ganged enclosures Works with steel side panels only; will not accommodate wood side panels 	<table border="1"> <thead> <tr> <th>Part #</th> <th>CFM</th> </tr> </thead> <tbody> <tr> <td>5-FAN-K</td> <td>114</td> </tr> </tbody> </table> <p>includes 2 fans, 4 grilles, & vent blocker</p>	Part #	CFM	5-FAN-K	114	<table border="1"> <thead> <tr> <th>Part #</th> <th>Fits</th> </tr> </thead> <tbody> <tr> <td>5-RS20</td> <td>20" deep models</td> </tr> <tr> <td>5-RS26</td> <td>26" deep models</td> </tr> </tbody> </table> <p>low-friction bottom runners allow the Slim 5 to easily slide in and out of credenzas and lecterns</p>	Part #	Fits	5-RS20	20" deep models	5-RS26	26" deep models
Part #	Description																	
5-BAVTRIM	black brushed & anodized																	
Part #	CFM																	
5-FAN-K	114																	
Part #	Fits																	
5-RS20	20" deep models																	
5-RS26	26" deep models																	



Top and side panels are constructed from thermolaminated MDF. Call for custom top when using cable chase.

WUSS and SH Series shelves need to be installed prior to installation of wood side panels, which conveniently lift off.




Removable Steel Side Panels are vented top and bottom with recessed lift handles and internal locking clips.

Finished in a durable black textured powder coat, each side panel adds 5/8" per side to overall enclosure width.



Doors are capable of being installed with a right or left swing and are equipped with a cam keylock and attractive flush handle.

Requires the use of a cable chase when used in multi-bay installations. Doors provide 1-1/2" clearance.



Rear access panels feature a unique no-hinge "tip-out lift-off" design with a two 4" fan laser knockout for cable pass-through on the bottom.






Securing keylock included.

Part #	Solid Front Door	Plexi Front Door	Steel Side Panels, Pair	Thermolaminate Top/Side Panels**	Rear Access Panel	Adjustable "Split" Rear Rackrail	Cable Chase 3" Wide*
5-8	D0-5-8	DOP-5-8	SP-5-8	-	RAP8	5AR8	5CC8
5-14	D0-5-14	DOP-5-14	SP-5-14	TSP-5-14xx	RAP14	5AR14	5CC14
5-21	D0-5-21	DOP-5-21	SP-5-21	TSP-5-21xx	RAP21	5AR21	5CC21
5-29	D0-5-29	DOP-5-29	SP-5-29	TSP-5-29xx	RAP29	5AR29	5CC29
5-37	D0-5-37	DOP-5-37	SP-5-37	TSP-5-37xx	RAP37	5AR37	5CC37
5-43	D0-5-43	DOP-5-43	SP-5-43	TSP-5-43xx	RAP43	5AR43	5CC43
5-8-26	D0-5-8	DOP-5-8	SP-5-8-26	-	RAP8	5AR8-26	5CC8-26
5-14-26	D0-5-14	DOP-5-14	SP-5-14-26	TSP-5-14-26xx	RAP14	5AR14-26	5CC14-26
5-21-26	D0-5-21	DOP-5-21	SP-5-21-26	TSP-5-21-26xx	RAP21	5AR21-26	5CC21-26
5-29-26	D0-5-29	DOP-5-29	SP-5-29-26	TSP-5-29-26xx	RAP29	5AR29-26	5CC29-26
5-37-26	D0-5-37	DOP-5-37	SP-5-37-26	TSP-5-37-26xx	RAP37	5AR37-26	5CC37-26
5-43-26	D0-5-43	DOP-5-43	SP-5-43-26	TSP-5-43-26xx	RAP43	5AR43-26	5CC43-26





*Custom width cable chases available, please call for details. ***Replace 'xx' with DS = Darkstone, GS = Graystone, PS = Pepperstone (Tops Only), SL = Slate (Sides Only) SG = Shark Gray, EA = Ebony Ash, WG = Wenge, DC = Dark Cherry, DP = Dark Pecan, AG = Aged Cherry, HM = Honey Maple, LW = Light Walnut, MP = Maple. See pg. 175 for thermolaminate finish options.











Branch Circuits and Receptacle Types

			15 Amp		
15 Amp	20 Amp		Up to 20 Circuits (60 outlets) 120V or 250V		
Up to 20 Circuits (40 outlets) 120V	Up to 20 Circuits (40 outlets) 120V			Up to 20 Circuits (20 outlets) 120V or 250V	Twist-Lock Up to 8 Circuits (8 outlets) 120V or 250V




Grounding

		Individual or Common Ground Conductors		
Non-Isolated	Isolated (Technical)	Surge Protection available for all circuits	Ground prong up or down	

Receptacle Colors - PDW strips can have up to 20 receptacles



							
White	Blue	Ivory	Grey	Brown	Black	Isolated Ground Outlets are only available in Orange	Twist-Lock Outlets are black (20 Amp and 30 Amp)

Terminations - Choice of top or bottom

		
Junction Box	Adapter Box & Nipple	Flexible 'Greenfield' Conduit
Available Sizes: (inches) 8L x 6W x 3H 8L x 5W x 3H 8L x 4W x 3H 6L x 6W x 3H	Adapter Box Size: 3L x 4W x 3H Nipple w/ locknut & bushing Trade Size: 1" or 1.25" Lengths: 2", 4" or 6"	Adapter Box Size: 3L x 4W x 3H Trade Size: 1" or 1.25" Length: 1ft. - 25ft. (All lengths include an insulated ground wire)*

* Per 2008 NEC article 250.118, all flexible metal conduit over 6ft. in length must include a separate grounding conductor.

Markings Customized to Your Specifications - permanently laser-engraved

	Custom Circuit/ Receptacle ID markings		Text and Graphics/Logos are also available
		Any custom logo or text can be laser etched on face	

Ordering is Easy

Use our intuitive online PDW configurator at www2.middleatlantic.com/PDW. Then submit online or by email (sales@middleatlantic.com).

