



PRODUCT INFORMATION SHEET

Standard Welding Cable

4/0 2052X30B WCAB BK

105°C - Class K Conductor

Conductor

| | | |
|-----------------------|---------------|------------------------|
| Size: | 4/0 | (103MM ²) |
| Number of Strands: | 2052 | |
| Strand Diameter, Nom: | 30GA | (0.26MM) |
| Conductor Area, Min: | 205,500 cmils | |
| Conductor: | Bare Copper | |
| Conductor Diameter: | 0.547 in | (13.89MM) |

Insulation

| | | |
|----------------------|------------|--------------|
| Insulation Material: | 105°C EPDM | |
| Min Wall: | 1.42 mm | (0.056 in) |
| Nom Wall: | 2.02 mm | (0.080 in) |
| Diameter, Min: | 17.79 mm | (0.700 in) |
| Diameter, Max: | 18.80 mm | (0.740 in) |
| Strip Force, Min: | 4 lbs. | (17.8 N) |
| Strip Force, Max: | 40 lbs. | (178.0 N) |
| Separator: | Physical | |

| | |
|---------------------|--|
| Voltage Rating: | 600V |
| Temperature Rating: | -40°C to 105°C |
| Specifications: | DPA: ES-1573 DPA: ES-235 (Strip Force) DPA: ES-215 (Print) |
| Part Number: | 151496-62 |
| Packaging: | Reels |
| Print Legend: | PRESTOLITE 4/0 GA. 600 VOLTS 105C MADE IN U.S.A. |
| Color: | Black |
| Other: | RoHS compliant |