




LAN CABLE

5E CMP

CMP(Plenum Rated)

Cable Structure



Test Standard

ISO / IEC 11801
ANSI / TIA-568.2-D
c(UL)

Construction & Specifications

- Conductor: Solid-Bare Copper 0.50±0.10mm
- Insulation: FEP 0.85±0.03mm
- Insulation Color:
 1. Blue & White with Blue
 2. Orange & White with Orange
 3. Green & White with Green
 4. Brown & White with Brown
- Rid cord:A Kevlar rip cord under jacket for ease of jacket stripping
- Jacket: Low Smoke PVC jacket 4.50±0.20mm

Jacket Physical Properties

Before Aging Tensile Strength (MPa)	≥ 13.5
Before Aging Elongation (%)	≥ 150
Aging Period (°C x hrs)	100°C x 24h x 7d
After Aging Tensile Strength (MPa)	≥12.5
After Aging Elongation (%)	≥ 125

Printing:

PSI DATA UTP CAT5E 4PR 24 AWG CMP (UL) c(UL) E***** FT6 VERIFIED TO ANSI/TIA - 568.2-D CAT 5e 350MHz RoHS 0000FT/1000FT

Remarks:

The information on this document is, to our knowledge, true and accurate. However, since the particular uses and the actual conditions of use of our products are beyond our control, establishing satisfactory performance of our products for the intended application is the customer's sole responsibility. All uses of PSI products and any written or oral information, suggestions or technical advice from PSI is without warranty, express or implied, and is not an inducement to use any product in conflict with any patent.

Electrical Performance (20 °C)

1.0-100.0 MHz Impedance (Ω) 100±15
 1.0-100.0 MHz Delay Shew (ns / 100m) ≤45
 Max DC Resistance (Ω/ 100m) 9.5
 Max DC Conductor Resistance Unbalance (%) 5.0

Technical Performance

MHz	RL ≥ dB	ATT ≤ dB	NEXT ≥ dB	PSNEXT ≥ dB
1	17	2.2	60	57
4	17	4.5	53.5	50.5
8	17	6.3	48.6	45.6
10	17	7.1	47	44
16	17	9.1	43.6	40.6
20	17	10.2	42	39
25	16	11.4	40.3	37.3
31.25	15.1	12.9	38.7	35.7
62.5	12.1	18.6	33.6	30.6
100	10	24	30.1	27.1
*200	9.0	34.4	25.8	22.8
*300	8.5	43.8	24.3	21.3
*350	8.0	46.9	22.1	19.1

Packing

1,000' Box / pallet

