

Technical data sheet · Metal fitting with shield termination TOP-T-S-EMV

Cable fittings and accessories



Identification	Type	TOP-T-S-EMV M 20 × 1.5
	Part-No.	600172
Use/Area of application		
Properties	<ul style="list-style-type: none">• Cable fitting with hexagon base• Strain relief• Gasket• O-Ring and EMC compliant shield termination• Simple installation - the shield braiding with plastic insert is pressed against fitting base	
Technical data		
Strain relief	Yes	
Material	Brass nickel-plated	
Protection class	IP 68 to 5 bar	
Gasket	Neoprene	
O-Ring (OR)	Perbunan®	
Clamping range D	8.0 – 13.0 mm	
weight approx.	2.88 kg/100 piece	
Thread	M 20	
Design		
G	M 20	
L 1	6.0 mm	

03.10.2009 – Subject to technical modification

Part-No. 600172

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Technical data sheet · Metal fitting with shield termination TOP-T-S-EMV


SW 22 mm

General

PU 100 piece

Note Simple installation - the shield braiding with plastic insert is pressed against fitting base.

Dimensions



d 11.5 mm

Certification



03.10.2009 – Subject to technical modification

Part-No. 600172

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



Systematic Technology