

# Lutze Cablefix Vario

## Modular Strain Relief System, with plastic or aluminum frame for cable assemblies



### Characteristics:

- Frame material
- Protection class

Polished Aluminum or Polyamide 66 (GF30)  
IP65

### Small (VK) Insert

#### Characteristics:

- Material
- Temperature range
- Resistance

TPE  
-40°C - +135°C,  
-40°F - +275°F  
UV, ozone, oils and fuels,  
acids and dyes, solvents  
and salt water

### Large (VG) Insert

#### Characteristics:

- Material
- Temperature range
- Resistance

TPE  
-40 - +135°C,  
-40°F - +275°F  
UV, ozone, oils and fuels,  
acids and dyes, solvents  
and salt water

### Blanking Plug

#### Characteristics:

- Material

PA6 (GF15)  
Gray

Part No.	Frame Type	Dimensions WxHxD in mm	No. of Small VK Inserts	No. of Large VG Inserts
<b>PLASTIC</b>				
<b>606050</b>	KKLR1	136 x 71 x 30	4	2
<b>606051</b>	KKLR2	164 x 71 x 30	6	3
<b>ALUMINUM</b>				
<b>606001</b>	AKLR1	108 x 68 x 30	4	2
<b>606002</b>	AKLR2	148 x 68 x 30	6	3
<b>606004</b>	AKLR4	148 x 108 x 30	12	6
<b>606005</b>	AKLR5	188 x 78 x 30	8	4
<b>606007</b>	AKLR7	188 x 118 x 30	16	8

Part No.	Type Small VK	Clamping Range mm	No of Holes
<b>606150</b>	VK0	SOLID	0
<b>606151</b>	VK4	4 – 4.5	14
<b>606152</b>	VK5	4.5 – 5.5	8
<b>606153</b>	VK6	5.5 – 6.5	8
<b>606154</b>	VK7	6.5 – 7.5	5
<b>606155</b>	VK8	7.5 – 8.5	5
<b>606156</b>	VK9	8.5 – 9.5	3
<b>606157</b>	VK10	9.5 – 10.5	3
<b>606158</b>	VK12	10.5 – 12.5	2
<b>606159</b>	VK14	12.5 – 14.5	2
<b>606160</b>	VK16	14.5 – 16.5	2

Part No.	Type Large VG	Clamping Range mm	No of Holes
<b>606200</b>	VG0	SOLID	0
<b>606201</b>	VG18	16.5 – 18.5	2
<b>606202</b>	VG20	18.5 – 20.5	1
<b>606203</b>	VG22	20.5 – 22.5	1
<b>606204</b>	VG24	22.5 – 24.5	1
<b>606205</b>	VG26	24.5 – 26.5	1
<b>606206</b>	VG28	26.5 – 28.5	1
<b>606207</b>	VG30	28.5 – 30.5	1
<b>606208</b>	VG32	30.5 – 32.5	1
<b>606209</b>	VG34	32.5 – 34.5	1

Part No.	Fits Insert Part No.	Type	Outer Dia. mm	Length mm
<b>606250</b>	606151	BL4	4	30
<b>606251</b>	606152	BL5	5	30
<b>606252</b>	606153	BL6	6	30
<b>606253</b>	606154	BL7	7	30
<b>606254</b>	606155	BL8	8	30
<b>606255</b>	606156	BL9	9	30
<b>606256</b>	606157	BL10	10	30
<b>606257</b>	606158	BL12	12	30
<b>606258</b>	606159	BL14	14	30
<b>606259</b>	606160	BL16	16	30
<b>606260</b>	606201	BL18	18	30

Specifications are subject to change without prior notice