



Liquidtight Flexible Metal Conduit High/Low Temp

TYPE - ATX



[Contact your local Sales Representative](#)
[Click Here for Printable Version](#)

Trade Size	Type	Inside Bend Radius	WT. (Lbs.)/100 Ft.	Carton Length	Part #	Reel Length	Part #	Reel Length	Part #	List Price
3/8"	ATX-10	1.5"	21	100	60201	500	60203	1000	60204	\$511.00
1/2"	ATX-11	2.0"	27	100	61201	500	61203	1000	61204	\$587.00
3/4"	ATX-12	2.5"	39	100	62202	500	62204	1000	62210	\$755.00
1"	ATX-13	3.0"	56	100	63202	400	63204	-	-	\$1,206.00
1-1/4"	ATX-14	3.5"	73	50	64202	200	64204	-	-	\$1,562.00
1-1/2"	ATX-15	4.5"	104	50	65202	150	65204	-	-	\$2,210.00
2"	ATX-16	5.5"	136	50	66202	100	66204	-	-	\$2,761.00
2-1/2"	ATX-17	8.0"	188	25	67202	-	-	-	-	\$5,794.00
3"	ATX-18	10.0"	210	25	68202	-	-	-	-	\$8,014.00
4"	ATX-19	12.0"	332	25	69202	-	-	-	-	\$12,619.00

See [Chart for Dimensions and Tolerances.](#)

TYPE - ATX

A non-UL conduit designed to withstand an extreme temperature range.

CONSTRUCTION:

Utilizes the flexibility of our standard LT core, coupled with the advantage of a thermoplastic rubber jacket that is virtually unaffected by temperature extremes and that contains no halogens. The material has a flammability rating of UL 94-HB and is UV stabilized.

APPLICATION:

Used in situations where concerns of resistance to temperature exposure exist. These include heavy outdoor equipment, boilers and furnaces, and sub-zero areas.



[WEEE and RoHS Compliant](#)

CE BS EN IEC 61386 Classification Code 445540650314

ARRA:

For ARRA Certification Letter, please [click here](#)

STANDARD COLORS:

Black. [Other colors available upon request](#)

WORKING TEMPERATURES:

-60°C to 150°C Intermittent to 165°C

For applications at the maximum rated working temperature of 150°C, Electri-Flex recommends the use of Thomas&Betts 5300HT series of liquidtight connectors. The gland ring and insulated throat in these fittings are rated for 150°C.

Flexibility: [See the Flexibility Comparison Guide](#)

Metal Used: Steel

Plastic Used: TPR [See the Type ATX - Chemical Resistance Guide](#)

High Mech. Strength	Listed For Direct Burial	Halogen Free	Low Fire Hazard	Accepts Standard Liquidtight Fittings	Self Extinguish	EMI/RFI Shielding	Oil Resistance	Acid Resistance
		X		X			X	

[Packaging, Disclaimer and Warranty](#)

© Electri-Flex Company 1-800-323-6174

[Privacy](#) [Terms](#)