

SILVYN® RILL PA 6

Non-Metallic, Flexible, Quick-Connect Conduit System



SILVYN® RILL PA 6 is a flexible, non-metallic corrugated conduit suitable for use in various industrial applications. It is resistant to liquids, oils, and gases, and highly resistant to acids and solvents. For use in controls, moving machine parts, motor and internal connections, and in industrial, medical, or electronic applications.

Application Advantage

- Halogen-free, flame retardant, and self-extinguishing
- Durable, long-lasting conduit is rugged yet flexible

Approvals



Complete the Installation



SILVYN®
KLIICK-G:
page 572



SILVYN®
KLIICK 90°:
page 573

Technical Data

Material:	Halogen- & silicone-free polyamide	Color:	Black (RAL 9005) Gray (RAL 7001)
Temperature Range:	-40°C to +115°C - Short-term: up to +150°C	Approvals:	V-0 per UL 94

Part Number	Outer Diameter	Inner Diameter	Bend Radius	Conduit Coil	Thread Size for Fittings		
					PG	NPT	Metric
61746935	0.394	0.256	0.512	164	PG 7	NPT 1/4"	M10 x 1.0
61746945	0.512	0.394	0.787	164	PG 9	NPT 1/4"	M12 x 1.5
61746955	0.622	0.472	1.378	164	PG 11	NPT 3/8"	M16 x 1.5
61747015	0.728	0.563	1.575	164	PG 13	—	—
61746965	0.835	0.650	1.772	164	PG 16	NPT 1/2"	M20 x 1.5
61746975	1.122	0.906	2.165	164	PG 21	NPT 3/4"	M25 x 1.5
61746985	1.358	1.142	2.559	82	PG 29	NPT 1"	M32 x 1.5
61746995	1.673	1.417	3.543	82	PG 36	NPT 1 1/4"	M40 x 1.5
61747005	2.146	1.890	3.937	82	PG 48	NPT 1 1/2"	M50 x 1.5

Photographs are not to scale and are not true representations of the products in question. For current information go to our website. If not otherwise specified, all values relating to the product are nominal values.