

638AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

**Picture
Not Available**

For more Information
please call

1-800-Belden1



General Description:

Access Control Cable, Plenum-CMP, 3-18 AWG pairs, 4-16 AWG conductors, 4-18 AWG conductors, 2-18 AWG conductors, All conductors stranded bare copper with Flamarrest® insulation, Each cable has overall Beldfoil® shield and Flamarrest® jacket, Banana Peel® No overall jacket

Usage (Overall)

Suitable Applications: Access Control

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
3	18	7x26	BC - Bare Copper	0.047

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.064

Twisted Pair Color Code Chart:

Number	Color	Description
1	Black and Red	Card Reader 1
2	White and Green	Card Reader 2
3	Orange and Brown	Card Reader 3

Individual Shield

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	(7x32)	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Nom. Dia. (in.)
0.291

Outer Jacket Ripcord: Yes

Outer Jacket Color Code Chart:

Number	Color	Description
1	Orange	Card Reader

Applicable Specifications and Agency Compliance

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

NEC Articles: 800

CEC/C(UL) Specification: CMP

Flame Test

UL Flame Test: NFPA 262

Suitability

Suitability - Indoor: Yes

638AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
72.000

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
40.000

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.600

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 6.900 Ohm/1000 ft

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Description	Current
Card Reader	4 amps @ 25C ambient temperature

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
2	18	7x26	BC - Bare Copper	0.047
4	18	7x26	BC - Bare Copper	0.047
4	16	19x30	BC - Bare Copper	0.057

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)	AWG
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.064	18
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.075	16

Insulation Color Code Chart:

Number	Color	Description
1	Black	Door Contact 1
2	Red	Door Contact 2
3	Black	Rex/Spare 1
4	Red	Rex/Spare 2
5	White	Rex/Spare 3
6	Green	Rex/Spare 4
7	Black	Lock/Power 1
8	Red	Lock/Power 2
9	White	Lock/Power 3
10	Green	Lock/Power 4

Individual Shield

Outer Shield

Outer Shield Material:

AWG	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)	Description
18	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Door Contact
18	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Rex/Spare
16	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Lock/Power

Outer Shield Drain Wire AWG:

Component	AWG	Stranding	Drain Wire Conductor Material
Door Contact	24	(7x32)	TC - Tinned Copper
Rex/Spare	24	(7x32)	TC - Tinned Copper
Lock/Power	24	(7x32)	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Outer Jacket Diameter:

Component #	Nom. Dia. (in.)
Door Contact	0.168
Rex/Spare	0.197

638AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Lock/Power	0.224
------------	-------

Outer Jacket Ripcord: Yes

Outer Jacket Color Code Chart:

Number	Color	Description
1	White	Door Contact
2	Blue	Rex/Spare
3	Gray	Lock/Power

Applicable Specifications and Agency Compliance

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

NEC Articles: 800

CEC/C(UL) Specification: CMP

Flame Test

UL Flame Test: NFPA 262

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Description	Freq. (MHz)	Capacitance (pF/ft)
Door Contact	1.000	126.000
Rex/Spare	1.000	76.000
Lock Power	1.000	81.000

Nom. Capacitance Conductor to Conductor:

Description	Freq. (MHz)	Capacitance (pF/ft)
Door Contact	1.000	70.000
Rex/Spare	1.000	42.000
Lock Power	1.000	45.000

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Door Contact	6.600
Rex/Spare	6.600
Lock Power	4.000

Nominal Outer Shield DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Door Contact	15.900
Rex/Spare	14.400
Lock Power	14.400

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Description	Current
Door Contact	4 Amps @ 25C ambient temperature
Rex/Spare	4 Amps @ 25C ambient temperature
Lock Power	5 Amps @ 25C ambient temperature

Physical Characteristics (Overall)

Conductor

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

Overall Cable

Overall Nominal Diameter: 0.542 in.

Mechanical Characteristics (Overall)

Bulk Cable Weight: 175 lbs/1000 ft.

Max. Recommended Pulling Tension: 428 lbs.

Min. Bend Radius/Minor Axis: 5 in.

638AFS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Applicable Patents:

Country
www.belden.com/p

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	538AFS

Notes (Overall)

Notes: Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
638AFS 0001000	1,000 FT	183.000 LB	NATURAL	C	4C16 + 4C18 + 3P18 + 2C18 SHLD

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 01-19-2015

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.