




TYPE - BR



[Contact your local Sales Representative](#)
[Click Here for Printable Version](#)

Trade	Type	Inner Diameter Min / Max	Outer Diameter Min / Max	Inside Bend Radius	Wt. (Lbs.) / 100 Ft.	Coil Length	Coil Part #	Coil Length	Coil Part #	Coil Length	Coil Part #	Coil Length	Coil Part #	Reel Length	Reel Part #	List Price Price Per 100 FT
3/8"	BR-10	.375 / .393	.560 / .610	2.0"	18	25	69308	50	69309	100	69301	250	69302	1000	69304	\$66.00
1/2"	BR-11	.625 / .645	.860 / .920	3.0"	28	25	69318	50	69319	100	69311	-	-	1000	69312	\$76.00
3/4"	BR-12	.812 / .835	1.045 / 1.105	4.0"	33	25	69328	50	69329	100	69322	-	-	500	69324	\$102.00
1"	BR-13	1.000 / 1.040	1.300 / 1.380	5.0"	52	25	69338	50	69332	-	-	-	-	400	69334	\$186.00
1-1/4"	BR-14	1.250 / 1.300	1.550 / 1.630	6.2"	65	-	-	50	69342	-	-	-	-	400	69344	\$241.00
1-1/2"	BR-15	1.500 / 1.575	1.850 / 1.950	7.5"	80	25	69352	-	-	-	-	-	-	300	69354	\$365.00
2"	BR-16	2.000 / 2.080	2.350 / 2.454	10.0"	99	25	69362	-	-	-	-	-	-	150	69364	\$455.00
2-1/2"	BR-17	2.500 / 2.700	2.860 / 3.060	12.5"	166	25	69372	-	-	-	-	-	-	-	-	\$587.00
3"	BR-18	3.000 / 3.200	3.360 / 3.560	15.0"	190	25	69382	-	-	-	-	-	-	-	-	\$978.00
3-1/2"	BR-350	3.500 / -	3.860 / 4.060	17.5"	170	25	69387	-	-	-	-	-	-	-	-	\$1,092.00
4"	BR-19	4.000 / -	4.360 / 4.560	20.0"	200	25	69392	-	-	-	-	-	-	-	-	\$1,243.00

Types BR and ABR Strip Profile



See [Chart for Dimensions and Tolerances.](#)

TYPE - BR

"BLUE RIBBON" (BR)

This non-jacketed flexible steel conduit has many universal wiring applications. It is often referred to as "Greenfield" or "Reduced Wall Flex".

CONSTRUCTION:

Type BR is formed from a highly corrosion-resistant, hot-dipped galvanized steel. Its profile and helical shape allow it to withstand substantial impact and crushing forces.


Meets federal specification A-A-55810 Type IV (Formerly, WW-C-566c Type II).

APPLICATION:

This conduit is intended for installation as a metal raceway for wires and cable in accordance with the NEC (ANSI/NFPA-70) Article 348.

- Suitable as an equipment grounding conductor (Section 250.118(5)).
- Wiring in elevators, hoist ways and escalators. (Section 620.21).
- Limit on use of 3/8 inch trade size. (Section 348.20)
- Raceway connection to motors (Section 430.223).
- Cranes and hoists (Section 610.11).
- Manufactured Wiring Systems - (Section 604.6(a)).
- Suitable for use with listed connectors intended for FMC (Flexible Metal Conduit).

Flexible metal conduit is also permitted for use on industrial machinery (ANSI/NFPA-79) (Section 14.5.4).

 Listed File #E53253 (sizes 3/8 through 3 inch). Conforms to Underwriters Laboratories Standard ANSI/UL-1 for Flexible Metal Conduit.

 Certified File #LL18858 (3/8 inch size only). Conforms to CSA 22.2 No. 56 for use per the Canadian electrical code C22.1 Section 12-1000.



[WEEE and RoHS Compliant](#)

ARRA:

For ARRA Certification Letter, please [click here](#)

Flexibility: [See the Flexibility Comparison Guide](#)

Metal Used: Steel

High Mech. Strength	Listed For Direct Burial	Halogen Free	Low Fire Hazard	Accepts Standard Liquidtight Fittings	Self Extinguish	EMI/RFI Shielding	Oil Resistance	Acid Resistance
X								

[Packaging, Disclaimer and Warranty](#)

® Electri-Flex Company 1-800-323-6174

[Privacy](#) [Terms](#)