


# LUTZE TOP-T Fittings EMC Metric and NPT

## Large Diameter Metal EMC (Electro Magnetic Compatibility), Quick Installation



### Characteristics

- Designed for large diameter cables
- Two seal inserts for clamping range adjustment
- Adapts to different size cable shields
- 360° shield termination
- Integrated strain relief
- Wide sealing and clamping range
- Fast and easy to install
- Temperature range -40°C - +80°C / -40°F - +176°F
- Protection class IP68

### Fitting Specifications

Connecting thread	Metric per EN 60423 NPT per ANSI ASME B1.21.1
Material	Brass, nickel plated
Clamping insert	Polyamide 6
Seal	CR Chloroprene Rubber
O-ring	NBR

### Approvals

- UL Listed as per UL2225

Specifications are subject to change without prior notice

Part No.	Thread	Clamping Range Ø inches	Clamping Range Ø mm	TL mm	SW1 mm	SW2 mm	H mm	UL R/L
<b>METRIC</b>								
<b>FMM63-CEX</b>	M63x1.5	1.378-1.771	35-45	20	68	64	43.5	L
<b>FMM75-CEX</b>	M75x1.5	1.812-2.440	46-62	20	80	80	51.0	L
<b>FMM90-CEX</b>	M90x1.5	2.363-2.952	60-75	20	95	95	55.0	L
<b>NPT</b>								
<b>FMNPT2-CEX</b>	NPT 2"	1.378-1.771	35-45	20	68	64	43.5	L
<b>FMNPT212-CEX</b>	NPT 2-1/2"	1.812-2.440	46-62	21	80	80	55.0	L
<b>FMNPT3-CEX</b>	NPT 3"	2.363-2.952	60-75	21	95	95	63.0	L

"These fittings are designed to provide strain relief and shield termination for large diameter VFD cables. They offer a wide sealing range with three removeable sealing rings".

